
STATE OF NEW MEX. 10 ENERGY AND MINERALS DEPARTMENT OIL CONSERVATION DIVISION

IN THE MATTER OF THE HEARING CALLED BY THE OIL CONSERVATION DIVISION FOR THE PURPOSE OF CONSIDERING:

AM.EXP.CO F - 7-17N-8W SANTA FE PACIFIC RAILROAD

CASE NO. 7923 Order No. R-4558-A

APPLICATION OF TESORO PETROLEUM CORPORATION FOR AMENDMENT OF DIVISION ORDER NO. R-4558 TO INCLUDE A POLYMER-AUGMENTED WATERFLOOD AND FOR APPROVAL OF A QUALIFIED TERTIARY OIL RECOVERY PROJECT UNDER THE CRUDE OIL WINDFALL PROFITS TAX ACT OF 1980, McKINLEY COUNTY, NEW MEXICO.



ORDER OF THE DIVISION

BY THE DIVISION:

This case came on for hearing at 9 a.m. on July 20, 1983, at Santa Fe, New Mexico, before Examiner Richard L. Stamets.

NOW, on this 30th day of August, 1983, the Division Director, having considered the testimony, the record, and the recommendations of the Examiner, and being fully advised in the premises,

FINDS:

- (1) That due public notice having been given as required by law, the Division has jurisdiction of this cause and the subject matter thereof.
- (2) That the applicant, Tesoro Petroleum Corporation, (hereinafter called Tesoro) seeks the amendment of Division Order No. R-4558 to expand the project area of its previously authorized secondary recovery project in the South Hospah Lower Sand Oil Pool for the conversion of existing water injection wells to polymer-augmented water injection wells, for the injection of polymer augmented water into said injection wells, and for the approval of the Tesoro South Hospah Lower Sand Oil Pool Project as a qualified tertiary recovery project under the Crude Oil Windfall Profits Tax Act of 1980.
- (3) That the waterflood project lies within the South Hospah Lower Sand Oil Pool, McKinley County, New Mexico.

- (4) That this pool was discovered in March, 1965, with development continuing until the present time, and that water injection into lease-line wells of the Tesoro South Hospah Lower Sand Oil Pool Project consisting of approximately 1055 acres was approved by said Division Order No. R-4558 on June 25, 1973, and water injection was commenced in September, 1973, and that further expansion of the pressure maintenance project occurred in November, 1980.
- (5) That the pressure maintenance project was subsequently administratively converted to a waterflood project.
- (6) That Tesoro now seeks approval for the injection of polymer-augmented water into 10 project wells as shown on Exhibit "A" attached to this order, and that the applicant seeks to obtain administrative approval in accordance with Rules 701, 702, and 703 of the Division Rules and Regulations for the drilling of new injection wells or the conversion of existing wells to be used for polymer-augmented water injection within the Project Area and the designation of its South Hospah Lower Sand Oil Pool Project as a qualified tertiary recovery project.
- (7) The proposed Qualifying Tertiary Project Area (QTP Area) lies wholly within the South Hospan Lower Sand Oil Pool and consists of the following described acreage:

TOWNSHIP 17 NORTH, RANGE 8 WEST, NMPM Section 6: Lot 6 (NW/4 SW/4) Lot 7 (SW/4 SW/4) E/2 SW/4 SE/4 S/2 NE/4

Section 7: Lot 1 (NW/4 NW/4) Lot 2 (SW/4 NW/4)

Lot 3 (NW/4 SW/4)

E/2 NW/4 W/2 NE/4 NE/4 NE/4

TOWNSHIP 17 NORTH, RANGE 9 WEST, NMPM Section 1: S/2 SE/4
NE/4 SE/4

Lot 9 Lot 10

(8) That the QTP Area is adequately delineated and that the entire area will be affected.

- That the New Mexico Oil Conservation Division has been designated by the Governor of the State of New Mexico as the appropriate agency to approve qualified tertiary recovery projects in New Mexico for purposes of the Crude Oil Windfall Profits Tax Act of 1980.
- (10) That the tertiary oil recovery method used in the Tesoro TTP Area is a polymer-augmented waterflood method which is a recognized tertiary oil recovery method described in Section 112.78 (c) of the Department of Energy Regulations in effect in June, 1979.
- (11 That the actual primary production from the Tesoro QTP Area prior to waterflooding was 752,675 barrels and as of March, 1983, secondary recovery operations had recovered an additional 266,156 barrels.
- (12 That an estimated 531,800 STB of additional oil or 3% of the triginal oil in place will be recovered as a result of the tertiary recovery operations, which is more than an insignificant increase in the amount of crude oil which will ultimately be recovered.
- (13 That the QTP Area tertiary recovery operations beginning date will be October 1, 1983.
- (14 That the QTP Area tertiary recovery operations paginning date is after May, 1979.
- (15) That the proposed tertiary recovery operations within the QTP Area meet all requirements of Section 4993 of the Internal Revenue Code.
- (16) That the Tesoro QTP Area project is designed in accordance with sound engineering principles.
- (17) That the injection wells or injection pressurization system should be so equipped as to limit injection pressure at the wellness to no more than 320 psi, but the Division Director should have authority to increase said pressure limitation, should consumstances warrant.
- (18) That Tesoro should survey all injection wells that empibit injection pressures significantly less than 320 psig.
- (19) That within 180 days of this order, applicant should conduct step-rate tests on those wells with injection pressures greater than 320 psig in order to establish the fracture gradient for those wells.

- (20) That the project area contains producing wells and plugged and abandoned wells for which insufficient data is available upon which to make a determination that such wells are not capable of serving as conduits for fluid migration from the injection zone.
- (21) That as of March, 1983, cumulative water injection into wells in said project totalled approximately 3.331 million barrels without apparent significant movement of injected fluid out of the injection interval.
- (22) That based upon this injection history, it appears that there may be no urgent need to institute repairs or replugging of any such wells.
- (23) That to assure continued injection within said project without endangerment to underground sources of drinking water, Tesoro should consult with the supervisor of the Division's district office at Aztec to:
 - (a) formulate an inspection plan to facilitate detection of injection well failure and/or out-of-zone injection fluid;
 - (b) repair any injection wellbore snowing evidence of fluid channeling or failure of tubular goods or packer;
 - (c) assure that all injection is through tubing under a packer; and
 - (d) formulate a plan for the repair, plugging, or replugging of any well in the project area as necessary to continue to assure that injection fluids do not magrate from the injection interval.
- of the pressure maintenance project as contained in Order No. R-4558 should be rescinded and the project should be provisions of Rule 701 through 13 and contained project as contained in Order No. under the provisions of Rule 701 through 13 and contained project as contained in Order No.
- (25) That the approval of this application will prevent waste, protect correlative rights and protect conservation.

IT IS THEREFORE ORDERED:

(1) That effective October 1, 1943, the limiting Tertiary Recovery Project Area, described in Finding No. (7) to

-5-Caled Mo. 7923 Orolar Mo. R-4558-A

This Irier, being the Tesoro South Hospah Lower Sand Oil Pool Profess McKinley County, New Mexico, is hereby certified as a limitated Tertiary Recovery Project under the Crude Oil Windfall Profits Tax Act of 1980.

- That the applicant, Tesoro, is hereby authorized to intest polymer-augmented water into the wells listed on Exhibit Lattached to this Order.
- That injection into the 10 wells listed on said Example "A" shall be authorized at a surface pressure of up to part subject to the following:
 - Tesoro shall survey all injection wells with injection pressure significantly less than 320 psig;

 - within 180 days of this Order, Tesoro shall conduct step-rate tests on those wells which exhibit injection pressures greater than 320 psig in order to establish a fracture gradient for each such well; and
 - (e the injection wells or systems shall be equipped to assure that the pressure limits determined under (d) above are not exceeded.
- (4 That except as provided under Order 3(d) above, the injection wells herein authorized and/or the injection pressure at the wellhead to no more than 320 psi, provided however, the Division Director may authorize a higher surface injection pressure upon satisfactory showing that such pressure will not result in fracturing of the confining strata.
- (5 That the special rules and regulations for operation of the tressure maintenance project as contained in Order No. 3--355 tre hereby rescinded and the project shall now be

operated under the Division's general oil and gas rules including Rules 701 through 708.

- (6) That the drilling of new injection wells or the conversion of existing wells to be used for polymer-augmented water injection shall be approved administratively under provisions of Division Rule 701.
- (7) That the operator shall consult with the supervisor of the Division's district office at Aztec to formulate a plan for the repair, plugging, replugging, or taking of other corrective action on any well in the project area as may be necessary to continue to assure that injected fluids do not migrate from the injection interval.
- (8) That jurisdiction of this cause is retained for the entry of such further orders as the Division may deem necessary.

DONE at Santa Fe, New Mexico, on the day and year herein above designated.

STATE OF NEW MEXICO

OIL CONSERVATION DIVISION

JOE D. RAMEY,

Director

SEAL

EXHIBIT "A"

- 1. Tenneco South Hospah Sand Unit Well No. 54
 1319' FNL and 5' FEL of Sec. 12, T-17-N, R-9-W
- 2. Tesoro Hanson Federal Well No. 197 1335' FSL and 1325' FWL of Sec. 6, T-17-N, R-8-W
- 3. Tesoro Eanson Federal Well No. 28 2310' FSL and 2310' FEL of Sec. 6, T-17-N, R-8-W
- 4. Tesoro Eanson Federal Well No. 34
 990' FSL and 2310' FEL of Sec. 6, T-17-N, R-8-W
- 5. Tesoro Santa Fe Well No. 10 330' FNL and 2310' FEL of Sec. 7, T-17-N, R-8-W
- 6. Tesoro Santa Fe Well No. 23
 5' FNL and 1330' FWL of Sec. 7, T-17-N, R-8-W
- 7. Tesoro Santa Fe Well No. 24 1335' FNL and 1325' FWL of Sec. 7, T-17-N, R-8-W
- 8. Tesoro Santa Fe Well No. 25 1220' FNL and 2600' FWL of Sec. 7, T-17-N, R-8-W
- 9. Tesoro Santa Fe "A" Well No. 84 5' FSL and 2900' FEL of Sec. 1, T-17-N, R-9-W
- 10. Tesoro Santa Fe "A" Well No. 87
 5' FSL and 50' FEL of Sec. 1, T-17-N, R-9-W

Case No. 7923 Order No. R-4558-A