

Gulf Oil Company - U.S.

EXPLORATION AND PRODUCTION DEPARTMENT
ROSWELL DISTRICT

T. W. Kidd
DISTRICT MANAGER
M. I. Taylor
DISTRICT PRODUCTION
MANAGER
P. E. Wyche
DISTRICT EXPLORATION
MANAGER
H. A. Rankin
DISTRICT SERVICES MANAGER

P. O. Drawer 1938
Roswell, New Mexico 88201

May 6, 1970

State of New Mexico
Oil and Gas Conservation Commission
1000 Rio Brazos Road
Aztec, New Mexico 87410

Re: Application for Permit to Drill
Torreon Working Interest Unit
No. 1, McKinley County, New Mexico

Gentlemen:

Please change the program as listed in our original Application dated April 30, 1970 to the following:

- (1) Drill 17-1/2" hole to 450' and run 13-3/8" casing to bottom.
- (2) After pressure testing casing, drill ahead with air mist with 11" hole to evaluate shows of oil or gas.
- (3) At 4200' run and cement a combination string of 8-5/8" casing, if needed, to protect exposed pay, correct loss circulation or control water flow.
- (4) If none of the events listed in three occur, reduce hole to 7-7/8" and continue drilling to Abo red bed or until water entry makes it necessary to mud-up.
- (5) Continue drilling with gel mud.

Yours very truly,

M. I. Taylor
M. I. Taylor

REA:mrd



A DIVISION OF GULF OIL CORPORATION

