Form Approved.

UNITED STATES DEPARTMENT OF THE INTERIOR

		Budget Bureau No. 42-R1424		
I	5.	LEASE		
		91-011596-14-20-0603-989		
i	6.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
-				
7. UNIT AGREEMENT NAME		UNIT AGREEMENT NAME		
		-		
_	8.	FARM OR LEASE NAME		
		Lone Pine Dakota "D" Unit		
_	9.	WELL NO.		
		16		
	10.	FIELD OR WILDCAT NAME		
		Basin Dakota		
	11.	SEC., T., R., M., OR BLK. AND SURVEY OR		
		Sec. 18, T17N, R8W		
	12.	COUNTY OR PARISH 13. STATE		
		McKinley New Mexico		
-	14.	API NO.		
	15.	ELEVATIONS (SHOW DF, KDB, AND WD)		

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME	
1 -:1	8. FARM OR LEASE NAME Lone Pine Dakota "D" Unit	
1. oil gas other	9. WELL NO.	
2. NAME OF OPERATOR	16	
Tenneco Oil Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Basin Dakota	
720 S. Colorado Blvd., Denver, CO 80222	11. SEC., T., R., M., OR BLK. AND SURVEY OF	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 18, T17N, R8W	
below.) AT SURFACE: 1700'FNL & 900'FEL, Unit H AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE McKinley New Mexico	
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.	
REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD 6996 KB	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zon	
PULL OR ALTER CASING MULTIPLE COMPLETE	change on Form 9–330.)	
CHANGE ZONES		
ABANDON* (other)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	e all pertinent details, and give pertinent dates irectionally drilled, give subsurface locations and it to this work.)*	
We propose to plug and abandon well via the f		
MIRUPU. NUBOE. Fill hole w/produced water. P Dakota perforations @ 2764'-2768' w/50 Sx cla CACL2 to 100' above perfs. Set cement plugs w CACL2 @ the following depths: جهن المحادة ال	ss "B" cement, 2% /class "B" cement, 2%	
RDMOPU. Install P&A marker. Clean, grade, and U.S.G.S. requirements.		
Subsurface Safety Valve: Manu. and Type	F1919F1	
18. I hereby ertify that the for going is true and correct	SEPER	
SIGNED SULLY PILLE Admin. Superv	isor DATE 9/12/79	
(This space for Federal or State offi	ice use)	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE	

*See Instructions on Reverse Side