UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	14-20-0603-9895
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plus baggs a difference of the proposals.) OF C 16 1981 and the proposals.	7. UNIT AGREEMENT NAME:
eservoir, use Form 9-331-C for such proposals.) NECTO 130	8. FARM OR LEASE NAME
1. oil gas well other OIL CON. COM.	Lone Pine Dakota D Unit
	9. WELL NO.
2. WANTE OF OPERATOR	16
Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Lone Pine Dakota D
720 S. Colo. Blvd., Denver, CO 80222	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1	7 AREA
below.) AT SURFACE: 1700'FNL, 900'FEL, Unit H	Sec. 18; T17N; R8W
AT SURFACE: 1/00 FNL, 900 FEL, Unit H AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH New Mexico
	14. API NO.
 CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA 	
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6996 KB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
RACTURE TREAT	and the analysis of the second
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	
MULTIPLE COMPLETE	
ABANDON*	SURVEY
other) FARMINGTON, N	
Table (por removal to the second to the	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
	ent to this work.y
12/6/79	
Tenneco Oil Company has plugged and abandoned the above well using the	
following procedure: 1. MIRUCU 6 Se	그 그는 그 생활을 하는 것이 된다.
0. 50	et cmt. plugs w/CL B cmt. 2% CACL2
G CIT	e following depths: 480'-350'
 Fill hole w/produced water POOH w/tubing 	73 1740'-1640'(25 sxs)
5 Saucozo Dakota noufountiana 7 Di	100'-Surface (25 sxs
	DMOPU DE A DE A DE LOS DE LA DELLA DE LA DELLA D
	nstall P& A marker
cmt. w/2% CACL2 to 100' above perfs. 9. C	lean, grade, and restore location
per l	JSGS requirements.
Subsurface Safety Valva: Many and Ton-	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
8. I hereby certify that the foregoing is true and correct	
IGNED ALLES MAINTILE Admin. Supervisor DATE 1/31/80	
(This space for Federal or State of Paymond W. VINY	
PPROVED BY	
CHOCHOUS OF REPROVAL, IF ANT:	