

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well based on a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980'FWL, 1980'FSL, Unit K  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
N00-C-14-20-3007

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Lone Pine Dakota D Unit

9. WELL NO.  
20

10. FIELD OR WILDCAT NAME  
Lone Pine Dakota D

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18, T17N; R8W

12. COUNTY OR PARISH  
McKinley

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6940'KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11/30/79

Tenneco Oil Company has pluggey & abandoned the above well using the following procedure:

1. MIRUCU
2. NUBOE
3. Fill hole w/produced water
4. POOH w/tubing
5. Squeeze Dakota perforations  
@ 2711'-2718' w/50 sxs CL B  
cmt. w/2% CACL2 to 100' above  
perfs.

6. Set cmt. plugs w/CL B cmt, 2% CACL2  
@ the following depths:  
470'-360'  
1650(25 sxs)  
100'-Surface (25 sxs)
7. RDMOPU
8. Install P&A marker
9. Clean, grade & restore location per  
USGS requirements.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carol J. Johnson TITLE Admin. Supervisor DATE 1/31/80

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) BATMAN W. WILKINS  
CONDITIONS OF APPROVAL, IF ANY:

TITLE ACTING DISTRICT SUPERVISOR DATE DEC 15 1981

NMOCC