

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Santa Fe R.R.
9. Well No. 30
10. Field and Pool, or Wildcat Hospah Dakota
12. County McKinley

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator Tesoro Petroleum Corporation
3. Address of Operator 8520 Crownhill, San Antonio, Texas 78209
4. Location of Well UNIT LETTER <u>N</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>17N</u> RANGE <u>8W</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 6892' GL, 6900' KB


Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
FULL OR PARTIAL CLOSING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well plugged and abandoned as follows:

Set 60-sack plug Class "C" cement (15#/gal) (230' plug) from total depth 2736' to 2506' (50' above Dakota "A"). Set 77-sack plug (300') from 1842' to 1542' (50' above, across, and 50' below the Upper Hospah, Lower Hospah, and Massive Gallup). Set 26-sack plug (100') from 675' to 575' (50' above and 50' into the Crevasse Canyon). Set 15-sack plug (50') from 50' to surface in 8-5/8" pipe. Dry hole marker has been installed and location is ready for inspection.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED K. H. [Signature] TITLE Manager of Prod. Engineering DATE July 27, 1972

APPROVED BY [Signature] TITLE Asst. Dir. III DATE 7-31-72

CONDITIONS OF APPROVAL, IF ANY: