

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-7772

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SIJNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. LEASE AGREEMENT NAME
2. NAME OF OPERATOR Eastern Petroleum Corporation	8. FARM OR LEASE NAME Hapertin
3. ADDRESS OF OPERATOR PO Box 291, Carri, Illinois 62821	9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface NW 1/4 Sec. 16, T-19-N, R-5-W, NMPM	10. FIELD AND POOL OR WILDCAT Hapertin
14. PERMIT NO. issued 1-6-73	11. SEC., T., R., M., OR BLM, AND SURVEY OR AREA T-19-N, R-5-W
15. ELEVATIONS (Show whether DE, RE, GR, etc.) 6580' RKB	12. COUNTY OR PARISH 13. STATE McKinley New Mex.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Propose to P&A this well starting Oct. 15, 1974. Geologic Markers are as follows: Cliff House 357', Menefee 458', Ft. Lookout 918', Mancos 2042', Dalton sd 2865', Gallup 2990', TD 3083'. 9 5/8"-63' w/75 sxs., 5 1/2"-2892' w/150 sxs., 4" liner 3071' w/24 sxs. (Top liner 2777').
Propose pulling 5 1/2" csg; setting plugs as directed; erect dry hole marker & clean location.
Plugging sequence: TD to 2980' - 100' plug on step 5 1/2" csg. @ 1850'; 100' plug 1850'-1950'; if 5 1/2" not pulled - 100' plug 300'-400'; 10 sxs. at surface.

18. I hereby certify that the foregoing is true and correct

TENNOCO OIL COMPANY
SIGNED *[Signature]*

TITLE Sr. Landman

DATE Oct. 1, 1974

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE