

Submit 3 Copies

to Appropriate

District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO. 30-031-20405
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SANTA FE PACIFIC RAILROAD
8. Well No. 11
9. Pool name or Wildcat Miguel Creek Gallup

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER: _____	
2. Name of Operator ROBERT L. BAYLESS	
3. Address of Operator P.O. BOX 168 FARMINGTON, NM 87499	
4. Well Location Unit Letter G : 1660 Feet from the NORTH Line and 1650 Feet from The EAST Line Section 29 Township 16N Range 6W NMPM McKINLEY County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6424 GL, 6429 RT	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO :	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER: _____	
SUBSEQUENT REPORT OF :	
REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: _____	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) **SEE RULE 1103.**

Robert L. Bayless intends to plug and abandon this well in 1999.

NOTED: AZTEC OGD
IN TIME TO WITNESS

RECEIVED
JUN - 9 1999
OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tom McCarthy TITLE ENGINEER DATE 5/10/99

TYPE OR PRINT NAME Tom McCarthy TELEPHONE NO. (505) 327-2659

(This space for State Use)
ORIGINAL SIGNED BY CHARLIE T. PEREZ

APPROVED BY _____ TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 3 DATE JUN 9 1999

CONDITIONS OF APPROVAL, IF ANY:

* Surface shoe Aug
Pelt 75' Below shoe

Robert L. Bayless

Plug and Abandon Procedure

SFPRR No. 11

1660' FNL & 1650' FEL, Section 29, T16N, R6W

McKinley County, NM

Well data:

Surface Casing: 7" 20# surface casing set at 64'. Cemented with 12 sx.

Production Casing: 4.5" 9.5# casing set at 731'. Cemented with 75 sx in 6 1/4" hole.

TD: 3062'

PBD: 754'

Perfs: 731-754' open hole.

Tubing: 2 3/8" 726'

Rods: 3/4' & 5/8"

1. Install rig anchors if necessary. Dig small workover pit if necessary.
2. Move in rig.
3. If well has rods, unseat pump and move rods to see if they are free. Reseat pump and pressure test tubing to 1000 PSI. Trip out laying down rods and pump.
4. Pick up extra tubing and tag PBD. Trip out and tally tubing. Inspect tubing. Pick up work string if necessary.
5. Trip in with tubing open ended. Tag PBD and raise tubing 2'. Circulate casing clean. Spot balanced **Cement Plug No. 1** (see volume below) down tubing. Trip out above cement and WOC. Trip in and tag cement. Spot additional plug if necessary.
6. Trip out with tubing to 100'.
7. Spot **Cement Plug No. 2** (see volume below) circulating to surface. Trip out with tubing. Shut in and WOC.
8. Cut off casing. Fill casings with cement if necessary. Install P & A marker. Rig down and move off.

Cement Plug No. 1: 20 sx.

Cement Plug No. 2: 45 sx.

Notes: All cement will be Class B Neat.

Other than the cement, the well bore fluid will be 8.3 PPG water.

All cement volumes will be 100% excess outside casing and 50' excess inside casing.