

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	1
LAND OFFICE	1
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator CHACO OIL COMPANY		8. Farm or Lease Name Santa Fe Pacific
3. Address of Operator P. O. Box 537; Farmington, New Mexico 87401		9. Well No. 38
4. Location of Well UNIT LETTER 0 , 275 FEET FROM THE South LINE AND 2510 FEET FROM THE East LINE, SECTION 20 , TOWNSHIP 20N , RANGE 9W NMPM.		10. Field and Pool, or Wildcat Red Mtn Mesaverde
15. Elevation (Show whether DF, RT, GR, etc.) 6488 GR		12. County McKinley

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input checked="" type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOBS	<input checked="" type="checkbox"/>		
OTHER	<input type="checkbox"/>		

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 10/19/74. Drilled 6 3/4" hole to 469'. Cored 469-474. Ran Century Geophysical E-log. Reamed core hole to 6 3/4". Ran & cemented 22 joints (459') 4 1/2", 9.5# new casing at 459' GL w/cement basket on bottom. Used 25 sx cement. Left open-hole 459-74. Drilled out plug & 10 feet cement. Washed to bottom. Pressure tested casing to 450 lbs. Held ok. Moved off rig 10/29/74. Will attempt completion later as oil well

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Sam C. Blair* TITLE Consulting Geologist DATE 2/3/75

Original *Blair* APPROVED BY *Blair* TITLE *Blair* DATE FEB 5 1975

CONDITIONS OF APPROVAL, IF ANY: