

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Colorado Plateau Geological Services, Inc.	8. Farm or Lease Name SFP - Blackjack
3. Address of Operator P. O. Box 537, Farmington, New Mexico 87401	9. Well No. 1
4. Location of Well UNIT LETTER <u>B</u> <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>20N</u> RANGE <u>9W</u> NMPM.	10. Field and Pool, or Wildcat WC
15. Elevation (Show whether DF, RT, GR, etc.) 6460 GR 6467 DF	12. County McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:


PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/30/75 reamed 6 3/4" hole to 12 1/2" to 58'. Set 2 jts (56') 9 5/8" 32# surface casing @ 56' BGL w/25 sx cement. April 15 & 16, 1975 rigged up McGee Rig No. 1 Drilled out from surface @ 10:00 p.m. 4/16/75. Reamed 6 3/4" hole to 7 7/8" from base surface to 1070'. Drilled 7 7/8" hole to 3703' on 4/23/75. Ran Schlumberger IES surface to 3702'. Spotted cement plugs as follows as directed by NMOCC:

100' plug 3550 - 3450
200' plug 2800 - 2600
100' plug 1500 - 1400
5 sx plug base surface casing.

Job complete 8:00 p.m. 4/23/75. Released rig. Will notify NMOCC when depth marker is set and location cleaned up.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mark E. Weidner TITLE Vice President DATE 4/29/75

APPROVED Original Signed by J. E. Kendrick TITLE SUPERVISOR DIST. #3 DATE SEP 29 1975

CONDITIONS OF APPROVAL, IF ANY: