

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
9. WELL NO.
10. FIELD AND POOL, OR WILDCAT
11. SEC. T., R., M., OR BLK. AND
SECTION OR AREA
12. COUNTY OR PARISH
13. STATE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR George E. Coleman	8. FARM OR LEASE NAME Easter Flats
3. ADDRESS OF OPERATOR P.O. Box 1915, Farmington, New Mexico 87401	9. WELL NO. 4
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1900' FNL and 1980' FWL	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO.	11. SEC. T., R., M., OR BLK. AND SECTION OR AREA Sec 7, T20N, R5W
15. ELEVATIONS (SHOW whether 2, 3, 4, or etc.) 6722 GR	12. COUNTY OR PARISH McKinley
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other)	


(Note: Report results of multiple completion on Well Completion or Plug and Abandonment and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is discontinuously drilled, give subsurface locations and measured and true vertical depths for all intervals and zones pertinent to this work.)*

1-12-76 MIRU Rotary tools - Coleman Drilling Company. Drill 7 7/8" hole to total depth 2946 feet. Run LES and Density logs. Run 4 1/2" 10.5 # K-65 casing and set at 2941 feet. Cement with 230 sks 65-35 Poz with 12% D-20 and 12 1/2 # per sack D-24, 245 sacks 50-50 Poz 2% D-20 and 2% CaCl₂ followed by 70 sacks class "A" cement with 2% CaCl₂ and .9 gallons per sack latex. Plug down at 6:00 p.m. 1-16-76.

RECEIVED

1976



18. I hereby certify that the foregoing is true and correct

SIGNED *Jack D. Cook* Jack D. Cook TITLE Agent

DATE 3-3-76

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY: