

1
m

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Northern Minerals, Inc.	8. Farm or Lease Name Santa Fe Pacific RR
3. Address of Operator P. O. Box 2182 Santa Fe, New Mexico 87501	9. Well No. Moore No. 1
4. Location of Well UNIT LETTER <u>K</u> <u>2100</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>3</u> TOWNSHIP <u>17N</u> RANGE <u>8W</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 6847 GR	12. County McKinley

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 1-10-76, Set 58', 7" casing, cement circulated. Drilled 5 1/8" hole to 2895. Cored 1310-1830' (Hospah). Took DST'S 2352-2394, no recovery; 2278-2320, no recovery; 2220-62, no recovery. 1762-1804 (Hospah), Rec. 480' muddy water.

1/23/76 Spotted cement Plugs: 2850-2750-100' Dakota
1900-1750-150' Gallup
700-600-100' Pt. Lookout
5 sacks in surface casing.

2/13/76 Set Dry-hole marker and cleaned up location. Ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mark E. Weidler
Mark E. Weidler

TITLE Consultant Geologist DATE 3/3/76

APPROVED BY AR Bendrick
CONDITIONS OF APPROVAL, IF ANY:

TITLE SUPERVISOR DIST. #3

DATE 3-16-76

