

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
NM 7250

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
EASTER FLATS #1

9. API Well No.
30-021-20479

10. Field and Pool, or Exploratory Area
FRANCISCAN LAKE MV

11. County or Parish, State
MCKINLEY NM

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

BASIN FUELS, LTD.

3. Address and Telephone No.

P.O. BOX 50 FARMINGTON, NM 87499 505-325-1701

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL x 330' FEL
SEC. 12 T20N R6W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent
 Subsequent Report
 Final Abandonment Notice

Abandonment
 Recompletion
 Plugging Back
 Casing Repair
 Altering Casing
 Other _____

Change of Plans
 New Construction
 Non-Routine Fracturing
 Water Shut-Off
 Conversion to Injection
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1.) THIS WELL WAS PLUGGED ACCORDING TO THE ATTACHED REPORT ON 9-20-96

2.) RESTORATION AND RESEEDING OF LOCATION WAS COMPLETED ON 10-30-96

RECEIVED
DEC 10 1996

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Grady W. Salzman

Title Agent

Date 12-5-96

(This space for Federal or State office use)

APPROVED

Approved by _____
Conditions of approval, if any:

Title _____

Date DEC 06 1996

/S/ Duane W. Spencer
DISTRICT MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

*See Instruction on Reverse Side

A - PLUS WELL SERVICE, INC.

P.O. BOX 1979
FARMINGTON, NM 87499
505-325-2627 • FAX: 505-325-1211

Well file

Basin Fuels Ltd.

September 23, 1996

Easter Flats #1 (Mesaverde)

2310' FNL, 330' FEL, Sec. 12, T-20-N, R-6-W

McKinley County, NM.,

NM 7250

Plug & Abandonment Report

Cementing Summary:

Plug #1 with 45 sxs Class B cement inside casing from 2216' to 1623' to cover Mesaverde perforations and top.

Plug #2 with retainer at 1367', mix 69 sxs Class B cement, squeeze 58 sxs outside 4-1/2" casing from 1420' to 1280' and leave 11 sxs inside casing to 1222' to cover Chacra top.

Plug #3 with 171 sxs Class B cement pumped down 4-1/2" casing from 658' to surface, circulate good cement out bradenhead.

Plugging Summary:

Notified BLM 6:00 am, 9/17/96

9-17-96 Safety Meeting. Pull rig onto location with rig up truck. RU rig and equipment. Bleed well down. Open up well, no pressure. Stack out rods. Move pump jack away from wellhead. Load tubing with 3 bbls water to pressure test to 500# for 5 min, held OK. Unseat pump. POH and LD 86 7/8" rods, 22' subs and pump. ND wellhead. NU BOP and test. RIH and tag bottom at 2216'. Plug #1 with 45 sxs Class B cement inside casing from 2216' to 1623' to cover Mesaverde perforations and top. POH and tally 69 joints 2-3/8" tubing. SI well. SDFD.

9-18-96 Safety Meeting. Open up well. Load casing with water. Pressure test casing to 500# for 5 min, held OK. Dig out wellhead. RU A-Plus wireline truck. Round-trip 4-1/2" gauge ring to 1380'. RIH and tag cement at 1687'. Perforate 3 HSC squeeze holes at 1420'. Establish rate into squeeze holes 1 bpm at 1000#. PU and RIH with 4-1/2" cement retainer; set at 1367'. Establish rate into squeeze holes 1-1/2 bpm at 1000#. Plug #2 with retainer at 1367', mix 69 sxs Class B cement, squeeze 58 sxs outside 4-1/2" casing from 1420' to 1280' and leave 11 sxs inside casing to 1222' to cover Chacra top. POH and LD tubing. Perforate 3 HSC squeeze holes at 658'. Establish circulation out bradenhead with 43 bbls water. Plug #3 with 171 sxs Class B cement pumped down 4-1/2" casing from 658' to surface, circulate good cement out bradenhead. Shut in well with 300# on casing and WOC. Chain up equipment. Pull alternator from PT #4. SDFD due to heavy rains and muddy location.

9-19-96 No activity due to muddy roads and location.

9-20-96 Safety Meeting. Open up well. ND BOP. Cut wellhead off, found cement at surface in 4-1/2" casing and annulus. Mix 10 sxs Class B cement and install P&A marker. RD rig and equipment. Move off location. Ronnie Snow with BLM on location.