STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

	_	
	1	
DISTRIBUTION		
SANTA FE	\top	
FILE		
U.S.G.S.		_
LAND OFFICE		
	_	_

CONDITIONS OF APPROVAL, IF ANY: See above.

OIL CONSERVATION DIVISION P. O. BOX 2088 SANTA FE, NEW MEXICO 87501

Form C-103 Revised 10-1-78

U.S.G.S.	
LAND OFFICE	5a. Indicate Type of Lease
OPERATOR	State X Fee
	5. State Oil 6 Gas Lease No.
CINDDA	16-2779.
100 NOT USE THIS FORM FOR PROPERTIES TO BELLEN OF STREET ON WELLS	
SUNDRY NOTICES AND REPORTS ON WELLS USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.) 1.	
· · / · · - · · · · · · · · · · · · · · · ·	7. Unit Agreement Name
OIL SAS WELL OTHER-	-
2. Name of Operator	8. Form or Lease Name
GEO ENGINEERING INC.	o Lin of Lease Name
1 2. Address of Chefefor	STATE
DO ROY AGIL COLOR TO THE STATE OF THE STATE	9. Well No.
PO BOX 2966 SANTA FR, NY 87504-2966	6
	10. Field and Pool, or Wildcat
UNIT LETTER # . 330 PEET PROM THE LINE AND _990 FEET PROM	CHACO WASH MIV
THE ELINE, SECTION 25 TOWNSHIP 2011 RANGE 94 MMPM.	
NAPA.	
15. Elevation (Show whether DF, RT, GR, etc.)	
6422 (-R	12. County
	M9/WA
Check Appropriate Box To Indicate Nature of Notice, Report or Otl	ner Data
NOTICE OF INTENTION TO:	REPORT OF:
155524527	REPORT OF:
PERFORM REMEDIAL WORK	
	ALTERING CASING
COMMERCE DRILLING OPNS.	PLUG AND ABANDONMENT
CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER	
OTMER	
17. Describe Proposed or Completed Operations (Closely and U.)	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703.	estimated date of starting any proposed
·	estimated date of starting any proposed
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. CONDITIONS OF APPROVAL:	estimated date of starting any proposed
CONDITIONS OF APPROVAL:	estimated date of starting any proposed
·	estimated date of starting any proposed
CONDITIONS OF APPROVAL:	estimated date of starting any proposed
CONDITIONS OF APPROVAL:	estimated date of starting any proposed
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357').	estimated date of starting any proposed
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid.	estimated date of starting any proposed
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes.	
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes.	
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign.	estimated date of starting any proposed
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign.	
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign.	
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of	
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMOCD district office 48 hours in advance of commencement of work.	E (3
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work.	
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work.	E (3
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work. 6. Work must commence by June 20, 1986.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work. 6. Work must commence by June 20, 1986.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work. 6. Work must commence by June 20, 1986.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work. 6. Work must commence by June 20, 1986.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMOCD district office 48 hours in advance of commencement of work.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work. 6. Work must commence by June 20, 1986.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
CONDITIONS OF APPROVAL: 1. Set bridge plug no more than 50' above perforations (348'-357'). 2. Load hole with inert fluid. 3. Pressure test casing and bridge plug to 100 psi for 15 minutes. 4. Cap well. Clean location. Install well sign. 5. Notify the Aztec NMCCD district office 48 hours in advance of commencement of work. 6. Work must commence by June 20, 1986.	5 6 2 5 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7