

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other Instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-5980

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Filon Exploration Corporation

3. ADDRESS OF OPERATOR

c/o Minerals Management Inc.

501 Airport Dr., Suite 105, Farmington, N.M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

87401

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 21

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 21, T20N, R5W

12. COUNTY OR PARISH 13. STATE

McKinley N.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6775' GR 6787' KB

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

PULL OR ALTER CASING ☐

WATER SHUT-OFF ☐

REPAIRING WELL ☐

FRACTURE TREAT ☐

MULTIPLE COMPLETE ☐

FRACTURE TREATMENT ☐

ALTERING CASING ☐

SHOOT OR ACIDIZE ☐

ABANDON* ☐

SHOOTING OR ACIDIZING ☐

ABANDONMENT* ☐

REPAIR WELL ☐

CHANGE PLANS ☐

(Other) Production Casing ☒

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-9-76

Drill to 5890'. Ran 171 joints (5858') 7" 23# LT&C casing.
Set at 5870' KB. Cement with 340 sx Halliburton Lite followed
with 100 sx Class "B". Did not circulate. Top of cement
by temperature survey at 3575'.

8-11-76

Drill 6 1/8" hole to 6110'. Ran 10 joints (420') 4 1/2" 10.5#
liner. Set at 6109' and cemented with 50 sx Latex Cement.
Circulate cement. Plug down at 5:30 AM 8-13-76.

RECEIVED

AUG 19 1976

U. S. GEOLOGICAL SURVEY
BUREAU, COLO.

AUG 20 1976

COM.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

J. Arnold Shell

TITLE

Area Manager

Minerals Management Inc. DATE 8-16-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: