

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N00-C-14-20-5377

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Allotted

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo Allotted 15

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Undesignated Entrada

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 15, T19N, R5W

12. COUNTY OR PARISH 13. STATE

McKinley N.M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Dome Petroleum Corporation

3. ADDRESS OF OPERATOR Minerals Management Inc., Suite 105,
501 Airport Drive, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310' FSL, 990' FWL, SEC. 15, T19N, R5W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6630' GR, 6642' KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Production Casing

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*


4-9-77

Ran 133 jts (5420') 7" OD, 23#, K-55 CSG. set at 5406' KB.
Cemented in two stages: 1st stage--450 sx 65-35 Poz, 6% Gel,
10# Gilsonite/sx tailed in with 100 sx Class "B" with 10% salt.

2nd stage--415 sx 65-35 Poz, 6% Gel, 10# Gilsonite/sx tailed in
with 50 sx Class "B" with 10% salt. Circulated cement on both
stages.

Plug down at 5:30 p.m.

CONFIDENTIAL



18. I hereby certify that the foregoing is true and correct

SIGNED

Area Manager

TITLE Minerals Management Inc. DATE April 11, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side