

N. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator Reserve Oil, Inc.		8. Farm or Lease Name Reserve-Ladd Chacra Mesa
3. Address of Operator P. O. Box 5568, Denver, Colorado 80217		9. Well No. 1
4. Location of Well UNIT LETTER F 1750 FEET FROM THE North LINE AND 1980 FEET FROM West 9 18N 7W THE LINE, SECTION TOWNSHIP RANGE NMPM.		10. Field and Pool, or Wildcat Wildcat - Entrada
15. Elevation (Show whether DF, RT, GR, etc.) 6924' GR		12. County McKinley

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>


17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to TD of 5103'. Plugged & Abandoned the subject well by authority of verbal approval obtained from Al Kendrick, April 6, 1977, by Morris Jones. Plugging procedure as follows: Spotted down open ended drill pipe a total of 214 sx. of reg. Class "G" cement at the following intervals:

4850-4950' 34 sx.
3700-3800' 34 sx.
3400-3500' 34 sx.
2750-2900' 51 sx.
1500-1600' 34 sx.
216-266' 17 sx.

10 sx. to surface

Hole filled w/9#/gal chemical gel mud between cement plugs. Subsequent to filling mud pits and reserve pit and restoration of surface, the appropriate District Office of the Commission will be contacted for a surface location inspection.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jack C. Bendler TITLE Div. Oper. Superintendent DATE 4-25-77

APPROVED BY Al Kendrick TITLE Director DATE 2-15-78
CONDITIONS OF APPROVAL, IF ANY:

4-25-78
A.L.