

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division


Sundry Notices and Reports on Wells

1. Type of Well
Oil

2. Name of Operator
NERDLIHC

3. Address & Phone No. of Operator
C/O NMOCD, 1000 Rio Brazos Road, Aztec, NM 87410

4. Location of Well, Footage, Sec., T, R, M
Sec 19. T-16-N, R-9-W, NMPM, McKinley County
Unit D, 330' FNL and 330' FWL



API # (assigned by OCD)
30-031-20507

5. Lease Number
Fee

6. State Oil & Gas Lease #
Fee

7. Lease Name/Unit Name
Bullseye

8. Well No.
#7

9. Pool Name or Wildcat

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

This well was plugged under NMOCD Contract #00-521-25-205 per attached work report.

SIGNATURE

William F. Clark

William F. Clark, President, A-Plus Well

January 8, 2001

(This space for State Use)

Approved by

ORIGINAL SIGNED BY E. VILLANUEVA

Title

DEPUTY OIL & GAS INSPECTOR, DIST.

Date

JAN - 8 2001

Daily Report

A - PLUS WELL SERVICE

16904

P.O. BOX 1979 • FARMINGTON, NM 87499
505-325-2627 • FAX (505) 325-1211Rig No #1Date MultipleWell No Ballseye #7Location D-19-16-9Company Nordlich

FROM	TO	DESCRIPTION OF OPERATION
Sept 2000		MO RA, Pull and LD 1 joint 2 3/8" thy.
Oct 30, 2000		Wireline - Bruce Martin NMICD
2.00		Ran 5 1/2" gauge ring to 1480' - had tag, procedure change approved by CIBU w/ NMICD, set 5 1/2" Plugwell
3.30		CIBU at 1475'.
THU 11-16-00		R-O GOOD & P-T #104, T/H with coiled TBG & TAG CIBU @ 1,484'. Load & circulate the hole clean with 26 BBLs water. Test CSG to 500' Hold 5 min OK. Plug #1 mix & Pump 12 SKS cement, from 1,484' to TAG @ 1,381'. PUGH with TBG to 980'. Load the hole with 1 1/2 BBL water. Plug #2 mix & Pump 30 SKS cement, from 980' to TAG @ 722'. PUGH with TBG to 258' circulate the hole clean. PUGH R-O EQUIP. MOD. Bruce Martin w/ NMICD as LOC.
MON 11-20-00		T/H with wireline & TAG TAG @ 730'. PUGH. HENRY VILLANUEVA w/ NMICD as LOC & OK'd TAG @ 730' & set to TOP off to 723'.
MON 12-4-00		DIG OUT & CUT OFF WELL HEAD. 9 5/8" CSG cement @ SURF. T/H with 1 1/4" coiled TBG TO 175'. Load the hole with 1 1/2 BBL water. Plug #3 mix & Pump 36 SKS cement, from 175' with good cement. Returns out the 5 1/2" CSG. PUGH with coiled TBG. Set marker & TOP off 5 1/2" CSG with cement left in coiled TBG. Bruce Martin w/ NMICD as LOC.
Dec 2000		Removed FANK: SEPARATOR

Fuel & Motor Oil _____ Water Hauled _____

Rental Equipment _____ Cement Retainers _____

Cementing P-#1-12 SKS P-#2-30 SKS P-#3-36 SKS + marker - 78 SKS -Wireline 5 1/2" CR, 5 1/2" Plugwell (CIBU) (bid. 70 SKS)

CREW	NAME	UNIT #	MILEAGE	HOURS
Supervisor	Bill Clark	45		
Operator	Robert Stuart	131		
Helper	Sam Stuart	161		
Helper				
Helper				