

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☒ gas well ☐ other
2. NAME OF OPERATOR  
DOME PETROLEUM CORP.
3. ADDRESS OF OPERATOR 501 Airport Drive,  
Suite #114, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 890' FSL, 1650' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
N00-C-14-20-5377
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Navajo Allotted
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Navajo Allotted #15
9. WELL NO.  
6
10. FIELD OR WILDCAT NAME  
Papers Wash-Entrada
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 15, T19N, R5W, N14PM
12. COUNTY OR PARISH: 13. STATE  
McKinley New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6553' GR, 6565' KB

(NOTE: Report results of multiple completion or zone change on Form 9-331-C)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/24/81: Moved in completion unit and rigged up. Replaced tubing head. Pulled 4½" plastic lined tubing. Tripped in hole with mill. Drilled Baker packer slips. Fished packer out of hole. Tripped in hole with bit and scraper. Cleaned hole out to 3362'. Ran Baker Retriva "D" Packer. Set packer at 2560'. Ran packer seal assembly and 65 joints new 4½", 10.5#, K55, ST&C tubing. Nippled up well head. Released rig 9/12/81.

Subsurface Safety Valve: Manuf. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Hollingsworth TITLE Area Prod. Supt. DATE October 20, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: