UNITED STATES ENT OF THE INTERIOR

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-7510-Bสิกผู้สิ่น โดยสิกผู้
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAE SORVET	
OUNDRY MOTIOFO AND DEPORTS ON WELLS	7. UNIT AGREEMENT NAME 900
SUNDRY NOTICES AND REPORTS ON WELLS	Value of the state
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8 FARM OR LEASE NAME
	Federal 22A and
1. oil 🔯 gas uell other	9. WELL NO. 70 8 2 3 5 4 7
2. NAME OF OPERATOR	2 2 2 5 5 5 6 8 L
Dome Petroleum Corp.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR % K&A, Inc. Minerals	Papers Wach Ent
Mgmt., 501 Airport Dr., Farmington, NM8740	111. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Sec. 22, T19N, R5W,	AREA Sec. 22, TI9N, RSW
below.) Sec. 22, Tign, R5W,	NMPM S T T S T
AT SURFACE: 2100' FSL, 2250' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	McKinley New Mexico
	14. API NO. 10 10 10 10 10 10 10 10 10 10 10 10 10
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	2084 8 8,53
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	6617' GREET & SECOT
TEST WATER SHUT-OFF	VIII
FRACTURE TREAT	action of the control
SHOOT OR ACIDIZE	
REPAIR WELL	978 NOTE: Report results of multiple completion or zone change on Form 9-330.
PULL OR ALTER CASING []	Change of Lording 20000
CHANGE ZONES	SURVEY THE BOTTON OF THE BOTT
ABANDON*	
(other) Spud & Surface Casing	그는 그는 한 시킨스템에 그를 잃었다면 다.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	e all pertinent details and give pertinent dates.
including estimated date of starting any proposed work. If well is d	irectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertiner	nt to this work.)* មួយដែល និក្សាស្ថិ
6-21-78 Spudded 12½" surface hole 2:00	PM. 44 22 2 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
Ran 5 jts., 202', 9 5/8" OD, 36	5#, K-55 ST&C casing
Set at 198' and cemented with 2	200 sx. Class B w/2% Cacl.
Circulated cement.	
Plug down at 9:30 PM.	
Ž	# # # # # # # # # # # # # # # # # # #
	19-18-
	26
	1 7011 COM. 1
and the second Time	OIL COME Set & Ft.
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct K&A, Inc.	. Minerals Management
Area Manage	
(This space for Federal or State of	fice use) នូវត្ស ប្រជាជាធិបាល បានទទួល បាន និងពី
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	
	E Standard Control of the Control of
	한가 되는 사람은 기를 받을 때 때문