H. S. GFOLOGICAL SURVEY

UNITED STATES DEPARTMENT OF THE INTERIOR

1373	HAUTED	CTATEC	1					
		STATES		5. LEASE		<u>É</u>	10 E E	
DEPAI	RTMENT O	F THE INTERIOR		NM -	7510-B 5	Ë	<u> </u>	
GEOLOGICAL SURVEY				6. IF IND	IAN, ALLOTTÉE 등들들	OR TRIE	BE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS The not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)				7. UNIT A	AGREEMENT NA	191	o, best ordina	
eservoir. Use Form 9-331-	-C for such prop	oosals.)			OR LEASE NAM	E Juli	indica indica	
1. oil gas					era1 22A =	<u> </u>	_ 유민은 - 변유공	
well well	9. WELL 2	NO. ခြင့်မြောင်း	<u>-</u> ਜ਼					
2. NAME OF OPERATOR					2 7 7 9 00 400 00 0 7 N		는 등 등 년 	
Dome Petrol	10. FIELD	OR WILDCAT N	AME	Migh frai tufs				
3. ADDRESS OF OPE	11 050	್ – ೯ ರ್ T., R., M., OR B	E ANE	S ÉLIBVEN	. OP			
Suite 107,	AREA	- ` - - > ∷	T19N.	R5W	OIL			
4. LOCATION OF WE		NMPM-	<u> </u>	ā55 5 ≳				
below.) Sec. 2 AT SURFACE: 2	12. COUN	TY OR PARISH	13. ST	ATE 2				
AT TOP PROD. IN	McKi	nley 등 등장		Mexio	c			
AT TOTAL DEPTH	14. API NO	D. = [F	릭활동법				
16. CHECK APPROPR		<u> </u>		<u> </u>				
REPORT, OR OTH	HER DATA				TIONS (SHOW	DF, KD	B, AND	WD)
REQUEST FOR APPRO	OVAL TO:	SUBSEQUENT R	EPORT OF:	0017	Gr.		; 	
TEST WATER SHUT-O						ž.	7135	
FRACTURE TREAT						blu	토물성 등	
SHOOT OR ACIDIZE				(NOTE: D-	port results of mu	.leinla oon	nalation or	7000
REPAIR WELL PULL OR ALTER CAS	ang 📙	H			ange on Form 9-		L C	
MULTIPLE COMPLETE						-		enoit
CHANGE ZONES						-		Ξ.
ABANDON*	X				1 출원맞춘	<u> </u>		1
(other)					<u> </u>	<u> 5.</u>	<u> 5 5 5 ₹</u>	
17. DESCRIBE PROPO including estimate measured and tru	ed date of sta	MPLETED OPERATION arting any proposed withs for all markers and	ork. It well is d	ilrectionally o	ittilea, give sub	give pe surface	rtinent di locations	ates, and
7/3/78 Ope	rator pro	poses to aband	lon subject			ق مصمورين		- N
Plu	ig No.	<u>Interval</u>	Length		s Cement	الما في المحتمر	5 th 18	-
	1	5100-5250	150'	7	5 sx = 5	18.00		
	2	4140-4290	150'		5 sx		18 12 E	
	3	2100-2250	150'		5 sx 1 2 = 5	JBL	235.49	78
	4	1930-2080	150' 50'		5 sx = 35 5 sx = 5 5	OU 507	20 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	· · ·
	5	175~ 225 0~ 30	30'		5 sx =	シルミンパ	15.6 B. 15.	<i>34.</i>
	6	0- 50	50	*		(ED:	19 i 32	
Telephone a	innroval i	received at 7:0	00 a.m. 7/3	3/78 from	Ed Schmit	t .	ختت	
rerephone a	.pprovar -			•	7 € 5.5 €	12 E		
					The figure in the first th	구동 일본		
							독립자회	
Subsurface Safety Valve: Manu. and Type					Set	@		Ft.
18. I hereby certify th	at the fore	ng is true and correct			225g9	÷		
TA	el h		lling & Pr	coduction	7/3/7	8 ^{3 5}		
SIGNED J. Arn	nold Snel	Sur	erintender	it		- E E	<u> </u>	
		(This space for I	ederal or State of	fice use)	[[[[[: E =	A Service of the serv	
APPROVED BY		TITLE		DA1	re 💢 🚘 🧒	77 Th 17	TO THE BE	
CONDITIONS OF APPRO				に起り	11			
						. S	真菌毒性	IJ
					E JUL	2 4 19	178	
						₩Æ IJ	1 U	

*See Instructions on Reverse Side