UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE	all and	na w gon: w an	
GEOLOGICAL SURVEY	NM-5981 6. IF INDIAN			
GEOLOGICAL SURVEY	J. 11 1110/111	3 E 2 G		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGE	REEMENTINA	ME S	্ হ
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)		2 8 B B	in the	,
	8. FARM OR Star La		initess fo loca	50 iba
1. oil	9. WELL NO	. 글 ^스 링및	9. g.t	26
2. NAME OF OPERATOR	11	년 5 1 년		<u>ਲ</u>
Engineering & Production Service, Inc.	10. FIELD OR Wildcat-		*	<u>.</u>
3. ADDRESS OF OPERATOR P.O. Box 190; Farmington, NM 87401	11. SEC., T.,			
	V DEV	00%5	n in 19 60	<u><u><u>g</u></u></u>
helow)	Sec.26-T20	N-RGW	in Sance	<u> </u>
AT SURFACE: 660' FNL & 660' FEL	12. COUNTY	OR PARISH	A. 11	<u> </u>
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	McKinley	or en	New Mexi	2
	14. API NO.	Haffin Tig th Suig t Suig t	onial ottima otto oni b	ő
.6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT. OR OTHER DATA	15 CLEVATIO			
	15. ELEVATIO 6710 G.L.	NS (SHOW	DF, KDB, AI	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0/10 G.L.	0 206 6	5 3 5 6	=
EST WATER SHUT-OFF		10 15 A	1 F69	ğ
FRACTURE TREAT		top much act	one cobi	5
REPAIR WELL	(NOTE: Report	္ င္ကို ္ကို t results of mu	ltiple completio	글 n or zone
PULL OR ALTER CASING	chang	e on Form 9-3	30.5 3 6 5	20 C
MULTIPLE COMPLETE	F.	2011 E	rel put put spte	ite:
ABANDON*	i i	bods bods	2 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	ion ion
other)	107	orle Hek Dan	the betgeous to the redmun entre branch bendietach in ibni and ibni a	ะสายได้สมระ ell operatio
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	all pertinent	ਰਾਹ ਤੋਂ ਵਾ lotails and		
including estimated date of starting any proposed work. If well is di	irectionally drille	ed, give sub	surface locati	ons and
measured and true vertical depths for all markers and zones pertinen	it to this work.)*	ping sprai sprai sprai	3 2 3	93 n
5-30-78: MIRU drilling rig - L & B speed dril	l spud wel	្រី (្វិ11:0	O A.M.	ertor:
5-30-78: Drill 11" hole to 87'. Ran 2 jts. 8	5/8" 20 0#	H-40 cs	a %0 set:	<u></u> 0
@ 83 ft. Cemented w/85 sks. Class "	'B" + 2% Ca	Cla. Ce	ment circ	u-
lated. Plug down @ 8:30 P.M. 5-30-7	8. WOC wi	Llinsta	ll:& test	
BOP prior to drilling out.			men With	tor.
		Syst of the system of the syst	bas onc onc aire	_ E
		200	Ledr How 12 CK	<u> </u>
		TO TO THE	at ta	gaittimdua
·		5 4 5 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	ble Federal Iaw and all all and was some are shown below or icable State require instructions.	2.2
		To Co	ea e	ນ . ປ
		tige of Britania (Control of Control of Cont	Sable Federal law and rejuical interpretations concerning are shown below of white interpretations.	benୟ ୟୁ. Ft.
Subsurface Safety Valve: Manu. and Type		Set (<u>u</u>	
18. I hereby certify that the loregoing is true and correct		Section of the sectio	cretes	250 21 11
Jack D. Cook STITLE Vice-President	DATE	=5-31-/8	25 38 1 36 38 2	<u> </u>
(This space for Federal or State office	ce use)	1: Pici	talot fu the fuly n	Ziri)
PPROVED BY TITLE	DATE	0 2 2 3	70	
CONDITIONS OF APPROVAL, IF ANY:		Die	雅 196	
		即歸事	de la constitución de la constit	မ်း ၂
		Pino:	Ser Ser	IU!
#San Instructions on Dayassa S	ida	" TUN	19 1 9 7 0 ²	