

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Basin Fuels, Inc.

3. ADDRESS OF OPERATOR 87401
300 W. Arrington, Suite 300, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2310' FSL & 330' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM-5979

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Jay Jay

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Franciscan Lake-Mesa Verde Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T20N, R5W

12. COUNTY OR PARISH
McKinley

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6733 GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-31-78: MIRU L&B speed drill. Spud well @ 3:00P.M. Drill 11" hole to 10' shutdown for rig repairs.

6-1-78: Drill 11" hole to 20'. Shut down for rig repairs.

6-2-78 thru 6-8-78: Rig repairs.

6-9-78: Rig down spud rig. MIRU 2nd L&B speed drill rig. Drill 11" hole to 90'. Ran 2 jts. 8 5/8" 20.0# H-40 ST&C csg & set @ 85'. Cement w/80 sks class "B" & 2% CaCl₂. Cement circ. Plug down 11:15 P.M. 6-9-78: WOC Will install & test BOP prior to drill out.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____

18. I hereby certify that the foregoing is true and correct

SIGNED Jack D. Cook TITLE Agent DATE 7-12-78

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
JUL 14 1978

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DENVER, COLO.