Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

LINITED STATES

DEPARTMENT OF THE INTERIOR	5. LEASE NM 8269
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other	Hospah 9. WELL NO.
2. NAME OF OPERATOR	64
Tenneco Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Lower Hospah South
720 S. Colo. Blvd., Denver, CO 80222	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec 12, T17N, R9W
AT SURFACE: 1360' FNL and 900' FEL, Unit H AT TOP-PROD: INTERVAL: AT IOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE NM NM
	14. API NO. 클로벌을 된 논설으로
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	1E FLEVATIONS (SUB) AND AND AND
HEI SKI, SK STILK BATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6938' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	0550 art
TEST WATER SHUT-OFF	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
FRACTURE TREAT	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	ကြောင်းသည်။ မြောင်းရှိသည်။ မြောင်းရှိသည်။ မြောင်းရှိသည်။ မြောင်းရှိသည်။ မြောင်းရှိသည်။ မြောင်းရှိသည်။ မြောင်းရ
ABANDON*	그 그는 그는 그를 생활하는 그 중에 독생하다는 것이다.
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	rectionally drilled, give subsurface locations and
11-3-78 to 11-5-78	
11 3 70 60 11 3 70	
Spudded 13 3/4" hole at 3:00 pm on 11-2-78 an	d continued drilling to 89'. Set
9 5/8", 36#, K-55 casing at 60' with 90 Sx of	Class B 2% CaCl cement Scirculated
cement to surface. Waited on cement. Tested	casing and BOP to 1000 for
30 minutes. Continued drilling to 1685'. Se	t 7", 23#, K-55 casing at 1680'
Cemented with 375 Sx of Class B, 2% CaCl and	circulated to surface. Released rig.
·	
	WAY 841979 11 11
1	JAN 2 COAL TOWN
Subsurface Safety Valve: Manu. and Type	OL CO Set @ Ft.
18. I hereby certify that the foregoing is true and correct	Lange of The Control
Valta .	elasto 6
SIGNED LISTLE Admin. Supervi	SUP DATE
(This space for Federal or State offi	ce use)
ADDOONED BY	
APPROVED BY TITLE TO CONDITIONS OF APPROVAL, IF ANY:	DATE
	79.