

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division


Sundry Notices and Reports on Wells

1. Type of Well
Oil

2. Name of Operator
NERDLIHC

3. Address & Phone No. of Operator
C/O NMOCD, 1000 Rio Brazos Road, Aztec, NM 87410

4. Location of Well, Footage, Sec., T, R, M
Sec 19, T-16-N, R-9-W, NMPM, McKinley County
Unit C, 430' FNL and 1750' FWL



API # (assigned by OCD)

30-031-20558 20556

5. Lease Number
Fee

6. State Oil & Gas Lease #
Fee

7. Lease Name/Unit Name
Bullseye

8. Well No.
#1Y

9. Pool Name or Wildcat

10. Elevation:

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

This well was plugged under NMOCD Contract #00-521-25-205 per attached work report.

SIGNATURE

William F. Clark
William F. Clark, President, A-Plus Well

January 8, 2001

(This space for Original Signed by E. VILLANUEVA)

DEPUTY OIL & GAS INSPECTOR, DIST. 8

Approved by _____ Title _____

Date _____

JAN - 8 2001

Rig No. #1 Date Multiple
Well No. Bullseye #14 Location C-14-16-9 Company Nerdline

FROM	TO	DESCRIPTION OF OPERATION
Sept 2000		Removed Tank Pole Unit MORA, Pull and LD 50 Hollow Rods, Pull and LD 57jts 2 3/8" tbg (170')
Wed 11-1-00		R-O wire line. T.H. with 4 1/2" Gauge Ring TO 1,788' POAH. T.H. & Set 4 1/2" Plug Well CIBP @ 1,728' POAH. R-O wire line. Bruce Martin w/ NMOGO on LOC.
Thu 11-16-00		R-O CURD & P-T #104. T.H. with coiled TBG & TAG CIBP @ 1,724'. Load & CIRCULATE The Hole Clean with 17 BBLs water. Test CS9 TO 500'. H2O 5 min CK. Plug #1 mix & Pump 12 SKS cement, ^{15.6"} From 1,724' TO TOC @ 1,566'. POAH with TBG TO 1,050'. Load The Hole with 1 BBL water. Plug #2 mix & Pump 24 SKS cement, ^{15.6"} From 1,050' TO TOC @ 734'. POAH with TBG TO 250'. CIRCULATE The Hole. POAH. R-O EQUIP. MOD. Henry Villanueva w/ NMOGO on LOC.
Mon 11-20-00		T.H. with wire line & TAG TOC @ 735' POAH. Henry Villanueva w/ NMOGO on LOC.
Mon 12-4-00		Dig out & cut well head off. 8 5/8" CS9 cement down 2' from surface. T.H. with 1 1/4" coiled TBG TO 140'. Load The Hole with 1 BBL water. Plug #3 mix & Pump 32 SKS cement, ^{15.6"} From 140' with good cement Returns out the 4 1/2" CS9. POAH with coiled TBG Set marker & top off 4 1/2" CS9 with cement left in coiled TBG. Bruce Martin w/ NMOGO on LOC.
Dec 2000		Removed 1- 300 bbl TANK 1- Pumping Unit

Fuel & Motor Oil _____ Water Hauled _____
Rental Equipment _____ Cement Retainers _____
Cementing P-#1-12 SKS ^{15.6"} P-#2-24 SKS ^{15.6"} P-#3-32 SKS & marker ^{15.6"} - 68 SKS - (65 bid)
Wireline 4 1/2" P-w/ CIBP @ 1,728'

CREW	NAME	UNIT #	MILEAGE	HOURS
Supervisor	R. Whitely	25		
Operator	S. STUART	161		
Helper				
Helper				
Helper				