NO. OF COPIES RECEIVED	12							Form C-10:		
DISTRIBUTION	<del>                                     </del>							Supersedes C-102 and		
SANTA FE	1-/1		NI	EW MEXIC	O OIL CON	SERVATION COMMISS	SION	Effective		
FILE	1-/-									
U.S.G.S.	$\perp$							5a. Indicate T	· ·	
LAND OFFICE								State	Fee.	LXI
OPERATOR	5							5. State Oil &	Gas Lease No.	
<del></del>										
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN ON PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)										
OIL XX GAS			OTHER-					7. Unit Agreen	nent Name	
2. Name of Operator								B. Form of Lease Name		
Fairfax Exploration, Inc.								Bullseye		
3. Address of Operator								9. Well No.		
301-B Graceland S.E. Albuquerque, New Mexico 87108							10		l	
4. Location of Well							10. Field and	Pool, or Wildcat		
UNIT LETTERO		3	30		South	LINE AND23	10	Wilde	at	i
		:								UUI
THE East	LINE, 9	ECTION_	18	TOWN:	16	N RANGE 9	<u> </u>			
	TTT	7777	1111 15.	Elevation	(Show whethe	r DF, RT, GR, etc.)		12. County	<del>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</del>	M
							:	McKi nley		
16.	<u> </u>	ملا لام	Deconiere	Bor To	Indiana	Name of Marine	P			77777
NOTI			ENTION .		indicate i	Nature of Notice,	•			
, 1011	CEU	- 1141	ENTION	10:			SUBSEQUEN	IT REPORT O	ri	
PERFORM REMEDIAL WORK	7			B: 116 AND	ABANDON	REMEDIAL WORK	<u> </u>	***		
TEMPORARILY ABANDON	<b>ゴ</b>			PEUT AND		COMMENCE DRILLING	. <u>.</u> H	-	TERING CASING	$\perp$
PULL OR ALTER CASING .	┥					COMMERCE DEILLING	······	PLI	IS AND ABANDONMEN	ut L
POCC ON ACICH CASING.				F 44 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	11 AMA XX					
				CHANGE P	LANS XX	CABING TEST AND CEM	ENT JQS .			
OTHER				CHANGE P	ILANS XX	CABING TEST AND CEM	ENT JQS			
OTHER			<del></del>	CHANGE P	LANS XX	' <b>i</b>	ENY JOB			
17. Describe Proposed or Co	emplete	nd Opera	ztions (Clea					ng cetimated date	of starting any pri	posed
	omplete	d Oper	ations (Clea					ng cetimated date	of starting any pri	posed
17. Describe Proposed or Co	emplete	d Oper	ations (Clea					ng cetimated date	of starting any pri	pposed
17. Describe Proposed or Co				viy state ai	il persinens de			ng cetimated date	of starting any pro	pposed
17. Describe Proposed or Co	1.	Dri	.11 105 <b>'</b>	urly state at	Il pertinent de	othentails, and give persinent		ng cetimated date	of starting any pro	posed
17. Describe Proposed or Co	1.	Dri Set	.11 105' : 100' 1	12 3/4 0 3/4"	Il pertinent de	tails, and give pertinent	detes, includis	:		pposed
17. Describe Proposed or Co	1.	Dri Set Dri	11 105' : 100' 1	12 3/4 0 3/4" 8" hole	# hole. surface	casing 41#.	detes, including	Core Hospa	h <b>-</b>	uposed
17. Describe Proposed or Co	1.	Dri Set Dri Gal	.11 105' : 100' 1 .11 7 7/ .1up San	12 3/4" 0 3/4" (8" hole	# hole. surface	othertails, and give pertinent	detes, including	Core Hospa	h <b>-</b>	uposed
17. Describe Proposed or Co	1.	Dri Set Dri Gal 14.	11 105' : 100' 1 :11 7 7/ :1up San :5# Casi	12 3/4 0 3/4" (8" hole ad, if c	# hole. surface	casing 41#.  pah-Gallup Sand	detes, including	Core Hospa	h <b>-</b>	nposed
17. Describe Proposed or Co	1. 2. 3.	Dri Set Dri Gal 14. Com	11 105' 100' 1 11 7 7/ 1up San 5# Casi p <b>le</b> te a H <b>os</b> pah-	12 3/4 0 3/4" 8" hole nd, if o	#" hole. surface to Hosp oil beari ah-Gallup	casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. oil bearing, dr	at 838',	Core Hospa nd set 5 1/	h- 2"	pposed
17. Describe Proposed or Co	1. 2. 3.	Dri Set Dri Gal 14. Com	11 105' 100' 1 11 7 7/ 1up San 5# Casi p <b>le</b> te a H <b>os</b> pah-	12 3/4 0 3/4" 8" hole nd, if o	#" hole. surface to Hosp oil beari ah-Gallup	casing 41#. casing up Sand	at 838',	Core Hospa nd set 5 1/	h- 2"	pposed
17. Describe Proposed or Co	1. 2. 3.	Dri Set Dri Gal 14. Com If Set Com	11 105' 100' 1 11 7 7/ 1up San 5# Casi nplete a Hospah- 5 1/2"	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon	" hole. surface to Hosp oil beari ah-Gallup is not of producti ta "A" We	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out of Well. coil bearing, dr con casing.	at 838', to 880' ar	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed
17. Describe Proposed or Co	1. 2. 3.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	pposed
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out of Well. coil bearing, dr con casing.	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	nposed .
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	pposed
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed .
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	Dposed .
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha	11 105' 100' 1 11 7 7/ lup San 5# Casi plete a Hospah- 5 1/2" pplete a	12 3/4 0 3/4" (8" hole nd, if cong. as Hospa Gallup 14.5# as Dakon	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out  Well. coll bearing, dr con casing. eto Bullseye t	at 838', to 880' and ill on to	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed
17. Describe Proposed or Co work) SEE RULE 1703.	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha Lea	11 105' 100' 1 11 7 7/ lup San 5# Casi nplete a Hospah- 5 1/2" nplete a ange Far ase name	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon om or Le (Reque	" hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name ested by	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out of Well. coil bearing, dr con casing. etc. etc Bullseye t Mr. Frank Chav	at 838', to 880' and ill on to conform ez).	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed
17. Describe Proposed or Co	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha Lea	11 105' 100' 1 11 7 7/ lup San 5# Casi nplete a Hospah- 5 1/2" nplete a ange Far ase name	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon om or Le (Reque	" hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name ested by	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out of Well. coil bearing, dr con casing. etc. etc Bullseye t Mr. Frank Chav	at 838', to 880' and ill on to conform ez).	Core Hospa nd set 5 1/ , Dakota "A"	h- 2" Sand.	uposed .
17. Describe Proposed or Co work) SEE RULE 1703.	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha Lea	11 105' 100' 1 11 7 7/ lup San 5# Casi nplete a Hospah- 5 1/2" nplete a ange Far ase name	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon om or Le (Reque	" hole. surface to Hosp oil beari ah-Gallup is not co producti ta "A" We ease name ested by	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out coll bearing, dr con casing. ell. e to Bullseye t Mr. Frank Chav	at 838', to 880' and ill on to conform ez).	Core Hospa nd set 5 1/ Dakota "A" with overa	h- 2" Sand.	
17. Describe Proposed or Co work) SEE RULE 1703.	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha Lea	11 105' 100' 1 11 7 7/ lup San 5# Casi nplete a Hospah- 5 1/2" nplete a ange Far ase name	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon om or Le (Reque	" hole. surface to Hosp oil beari ah-Gallup is not co producti ta "A" We ease name ested by	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out of Well. coil bearing, dr con casing. etc. etc Bullseye t Mr. Frank Chav	at 838', to 880' and ill on to conform ez).	Core Hospa nd set 5 1/ Dakota "A" with overa	h- 2" Sand.	
17. Describe Proposed or Co work) SEE RULE 1703.	1. 2. 3. 4. 5.	Dri Set Dri Gal 14. Com If Set Com Cha Lea	11 105' 100' 1 11 7 7/ lup San 5# Casi nplete a Hospah- 5 1/2" nplete a ange Far ase name	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon om or Le (Reque	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name ested by	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out coll bearing, dr con casing. ell. e to Bullseye t Mr. Frank Chav	at 838', to 880' and ill on to conform ez).	Core Hospand set 5 1/ Dakota "A" with overa	h- 2" Sand. 11	979
17. Describe Proposed or Co work) SEE RULE 1703.	1. 2. 3. 4. 5. 6. 7.	Dri Set Dri Gal 14. Com If Set Com Cha Lea	11 105' 100' 1 11 7 7/ lup San 5# Casi nplete a Hospah- 5 1/2" nplete a ange Far ase name	12 3/4 0 3/4" (8" hole ing. as Hospa Gallup 14.5# as Dakon om or Le (Reque	"hole. surface to Hosp oil beari ah-Gallup is not o producti ta "A" We ease name ested by	casing 41#. casing 41#. casing 41#. cah-Gallup Sand ng, drill out coll bearing, dr con casing. ell. e to Bullseye t Mr. Frank Chav	at 838', to 880' and ill on to conform ez).	Core Hospand set 5 1/ Dakota "A" with overa	h- 2" Sand.	979