

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator DOME PETROLEUM CORPORATION		8. Farm or Lease Name SANTA FE 33-20-10	
3. Address of Operator 501 Airport Drive, Suite 107, Farmington, NM 87401		9. Well No. 1	
4. Location of Well UNIT LETTER D, 900 FEET FROM THE NORTH LINE AND 700 FEET FROM THE WEST LINE, SECTION 33 TOWNSHIP 20N RANGE 10W NMPM.		10. Field and Pool, or Wildcat WILDCAT	
15. Elevation (Show whether DF, RT, GR, etc.) 6411' GR		12. County MCKINLEY	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER SPUD & SET SURFACE CASING <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 13½" hole at 9:45 PM, 01/28/80. Drilled to 200'. Ran 4 jts. (176') 9 5/8", 32.3#, H40, ST&C casing. Casing landed at 191' KB. Cemented with 200 sx. class "B" cement with 2% CaCl. Plug down at 7:00 AM, 01/29/80. Circulated cement.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. D. Hollingsworth TITLE DRILLING & PROD. FOREMAN DATE February 4, 1980

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE FEB 6 1980

CONDITIONS OF APPROVAL, IF ANY: