

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	4

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator DOME PETROLEUM CORPORATION	8. Farm or Lease Name Santa Fe 4-20-10
3. Address of Operator 501 Airport Drive, Suite 107, Farmington, New Mexico 87401	9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1700</u> FEET FROM THE <u>North</u> LINE AND <u>460</u> FEET FROM THE <u>East</u> LINE, SECTION <u>4</u> TOWNSHIP <u>20N</u> RANGE <u>10W</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 6241' GR	12. County McKinley

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Run Production Casing</u> <input checked="" type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 121 joints (5010') 7", 23# & 20#, K55, ST&C Casing. Casing landed at 5022' K.B. Cemented with 300 sacks 65/35 Pozmix with 6% gel and 10# Gilsonite/sack. Followed with 100 sacks Class "B" cement with 10% salt. Plug down at 5:45 P.M. 2/22/80.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>H. D. Hollingsworth</u>	TITLE <u>Drilling Production Foreman</u>	DATE <u>2/25/80</u>
APPROVED BY <u>Original Signed by FRANK T. CHAVEZ</u>		
CONDITIONS OF APPROVAL, IF ANY:		
SUPERVISOR DISTRICT # <u>3</u>		
DATE <u>MAR 10 1980</u>		