

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

LG 2779

7. Lease Name or Unit Agreement Name

State

8. Well No. 7

9. Pool name or Wildcat

Chaco Wash NW

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☐

OTHER H₂O Injection

2. Name of Operator

Brana Corporation

3. Address of Operator

320 Gold Ave. S.W., Suite 1223, Albuquerque, N.M. 87102

4. Well Location

Unit Letter A : 660 Feet From The North Line and 990 Feet From The East Line

Section 28 Township 20N Range 9W NMPM McKinley County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6421' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work to begin the week of October 14, 1991.

Casing: 4 1/2", 10.5 lb/ft casing set at 555' GR.

Cemented with 100 Sks class "B". Circulated cement.

PBTD: 350' GR

Perforations: 286'-306', 2 SPF.

312'-328', 2 SPF.

Proposed Plugging Procedure: Release packer set at 275' GR. TOOHw/tubing and packer. Lay down packer. TIH w/tubing. Set a 100ft cement plug from 328' to 228' GR with 8Sks(9.44CF) class "B" cement. Set a 50' cement plug at surface with 4Sks(4.72CF) class "B" cement. Install an appropriate dry hole marker.

RECEIVED

OCT 7 1991.

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Frank A. Welker TITLE Agent for Brana DATE 10-4-91

TYPE OR PRINT NAME Frank A. Welker TELEPHONE NO. 291-9502

(This space for State Use)

Original Signed by CHARLES GHOLSON

DEPUTY OIL & GAS INSPECTOR, DIST. #3

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

TOP PLUG 100' MINIMUM

OCT 07 1991

WELL # State #7 - Injection well

A Sec. 28 T. 20 N., R 9 W McKinley County
660' From N. line, 990' From E line

Casing: $4\frac{1}{2}"$ @ 555' GR.

Perfs.: 286' - 328'
501 - 509

T.D. 555' GR.

