

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well Oil</p> <p>2. Name of Operator Robert L. Bayless</p> <p>3. Address & Phone No. of Operator PO Box 168, Farmington, NM 87499 (505)327-2659</p> <p>4. Location of Well, Footage, Sec., T, R, M Unit P, 290' FSL and 330' FEL Section 20, T-16-N, R-6-W, NMPM, McKinley County</p>	<p style="text-align: center;">RECEIVED AUG 10 1999 OIL CON. DIV. PAGE 3</p> <p>5. API # (assigned by OCD) 30-031-20625</p> <p>6. Lease Number Fee</p> <p>7. State Oil&Gas Lease # Lease Name/Unit Name Santa Fe Pacific RR</p> <p>8. Well No. #27</p> <p>9. Pool Name or Wildcat Miguel Creek Gallup</p> <p>10. Elevation: 6406' GL</p>
--	---


Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

Robert L Bayless plugged and abandoned this well on July 15, 1999.

7-14-99 Road rig. RU. Attempt to PT tubing with 7 bbls water, no test. Unseat pump. LD 28 rods, 6 5/8" rods and 22 3/4" with pump. ND wellhead; NU BOP and test. RU tubing equipment. TOH and 23 joints and 10' mule shoe 2-3/8" EUE tubing, total 718'. Tubing looks good. TIH and tag at 748'. Circulate well clean with 6 bbls water. Plug #1 mix and pump 15 sxs Class B cement from 749' to 546'. TOH with tubing. Shut in well and WOC. SDFD.

7-15-99 TIH and tag cement at 593'. Attempt to PT casing to 500#, leak 1 bpm at 700#; established circulation out and around 4-1/2" casing. LD tubing. RU A-Plus wireline truck. Perforate 2 squeeze holes at 100'. Load casing and establish circulation around 4-1/2" casing. Plug #2 with 52 sxs Class B cement with 2% CaCl₂ from 100' to surface, circulate good cement around 4-1/2" casing. Shut in well and WOC. Open up well and tag cement at 2'. RD tubing equipment and ND BOP and wellhead. Dig out and cut off 4-1/2" casing. Mix 10 sxs Class B cement and install P&A marker. RD rig; move off location.
H. Villaneuva, NMOCD, was on location.

SIGNATURE	 Tom McCarthy	Engineer	August 4, 1999
-----------	---	----------	----------------

(This space for State Use)
Approved by ORIGINAL SIGNED BY E. VILLANEUVA Title DEPUTY OIL & GAS INSPECTOR Date AUG 10 1999