

11

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

**Sundry Notices and Reports on Wells**

1. **Type of Well**  
Oil

2. **Name of Operator**  
Robert L. Bayless

3. **Address & Phone No. of Operator**  
PO Box 168, Farmington, NM 87499 (505)327-2659

4. **Location of Well, Footage, Sec., T, R, M**  
Unit B, 990' FNL and 1650' FEL  
Section 29, T-16-N, R-6-W, NMPM, McKinley County

API # (assigned by OCD)  
30-031-20629

5. **Lease Number**  
Fee

6. **State Oil&Gas Lease #**  
**Lease Name/Unit Name**  
Santa Fe Pacific RR

8. **Well No.**  
#32

9. **Pool Name or Wildcat**  
Miguel Creek Gallup

10. **Elevation:**  
6419' GL

AUG 10 1999  
OIL CON. DIV.  
DIST. 3

**Type of Submission**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

**Type of Action**

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

**13. Describe Proposed or Completed Operations**

Robert L Bayless plugged and abandoned this well on July 28, 1999.

7-27-99 Repair roads and location. Rig crew pumping oil and water from pit on #23 to production tanks. MO, RU. Level rig on location; kept sinking. Load tubing with 1 bbl water and pressure test to 500#, held OK. Work pump pulling 15,000# and unseat. LD 28 rods, 11 5/8" and 17 3/4" with pump. Shut in well and SDFD.

7-28-99 Safety Meeting. ND wellhead and NU BOP, test. TOH and tally 23 joints with 10' mule shoe of 2-3/8" tubing, total 723'. TIH and tag bottom at 769'. Load and circulate well clean. Plug #1 with 29 sxs Class B cement with 2% CaCl<sub>2</sub> from 769' to 427'. TOH with tubing and WOC. TIH and tag cement at 438'. LD tubing. Load hole with 1-1/2 bbls water. Attempt to PT casing, leak, circulating around 4-1/2" casing. Perforate 2 squeeze holes at 100'. Establish circulation around 4-1/2" casing with 1/2 bbl water. Plug #2 with 16 sxs Class B cement with 2% CaCl<sub>2</sub> from 100' to surface with good cement returns around 4-1/2" casing. SI well and WOC. Tag cement at 3'. ND BOP. Dig out and cut off wellhead. Mix 8 sxs Class B cement and install marker. RD, MOL. H. Villaneuva, NMOCD, was on location.

SIGNATURE

Tom McCarthy

Engineer

August 5, 1999

(This space for use by E. VILLANUEVA  
Approved by \_\_\_\_\_

Title \_\_\_\_\_

DEPUTY OIL & GAS INSPECTOR, DIST. 3

Date \_\_\_\_\_

AUG 10 1999