


State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

**Sundry Notices and Reports on Wells**

<p>1. <b>Type of Well</b> Oil</p> <p>2. <b>Name of Operator</b> Robert L. Bayless</p> <p>3. <b>Address &amp; Phone No. of Operator</b> PO Box 168, Farmington, NM 87499 (505)327-2659</p> <p>4. <b>Location of Well, Footage, Sec., T, R, M</b> Unit B, 330' FNL and 2310' FEL Section 29, T-16-N, R-6-W, NMPM, McKinley County</p>	<p>API # (assigned by OCD) 30-031-20632</p> <p>5. <b>Lease Number</b> Fee</p> <p>6. <b>State Oil&amp;Gas Lease #</b></p> <p>7. <b>Lease Name/Unit Name</b> Santa Fe Pacific RR</p> <p>8. <b>Well No.</b> #35</p> <p>9. <b>Pool Name or Wildcat</b> Miguel Creek Gallup</p> <p>10. <b>Elevation:</b> 6419' GL</p>
---	--



**Type of Submission**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

**Type of Action**

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

**13. Describe Proposed or Completed Operations**

Robert L Bayless plugged and abandoned this well on July 29, 1999.

7-28-99 Road rig and equipment to location, RU. SDFD.

7-29-99 Safety Meeting. Load tubing with 1 bbl water and PT to 500#, held OK. Pull 28 rods, 14 5/8" and 14 3/4" with pump. ND wellhead and NU BOP, test. TOH and tally 24 joints 2-3/8" tubing with 18' mule shoe, total 764'. TIH and tag bottom at 768'. Load and circulate hole clean. Plug #1 with 25 sxs Class B cement with 2% CaCl<sub>2</sub> from 768' to 430'. TOH and WOC. TIH and tag cement at 483'. LD tubing. Load casing with 2 bbls water and PT to 500# for 5 min, held OK. Perforate 2 squeeze holes at 100'. Establish circulation around 4-1/2" casing with 4 bbls water. Plug #2 with 67 sxs Class B cement with 2% CaCl<sub>2</sub> from 100' to surface with good cement returns around 4-1/2" casing. SI well and WOC. Open up wellhead, cement at surface. ND BOP. Dig out and cutoff wellhead. Mix 5 sxs Class B cement and install P&A marker. RD, MOL.  
H. Villaneuva, NMOCD, was on location.

SIGNATURE

Tom McCarthy

Engineer

August 5, 1999

(This space for State Use)

Approved by

ORIGINAL SIGNED BY E. VILLANUEVA

Title

DEPUTY OIL & GAS INSPECTOR, DIST. 3

Date

AUG 10 1999