

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

IG-2779

7. Lease Name or Unit Agreement Name

State

8. Well No.

20

9. Pool name or Wildcat

Chaco Wash. NW

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL WELL ☐ GAS WELL ☐

OTHER H₂O Injection

2. Name of Operator

Brana Corporation

3. Address of Operator

320 Gold S.W., Suite 1223, ABQ., N.M. 87102

4. Well Location

Unit Letter A : 990 Feet From The North Line and 1315 Feet From The East Line

Section 28 Township 20N Range 9W NMPM McKinley County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6418'GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1101.

Work to begin the week of October 14, 1991.

Casing: 4½", 10.5 lb/ft set at 543'GR.

Cemented with 85 Sks class "B". Circulated cement.

FBTD: 543'GR.

Perforations: 295'-315'.

496'-503'.

Proposed Plugging Procedure:

Release packer set at 350'. TOOHw/tubing and packer. Lay down packer. TIH w/tubing. Set a 100' cement plug from 503' to 403' using 8 Sks(9.44CF) class "B" cement. Set a 100' cement plug from 315' to 215' using 8 Sks(9.44CF) class "B" cement. Set a 50' cement plug at surface, using 4 Sks(4.72CF) class "B" cement. Install an appropriate dry hole marker.

RECEIVED

OCT 7 1991

OIL CON. DIV.
DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Frank A. Welker TITLE Agent for Brana DATE 10-4-91

TYPE OR PRINT NAME Frank A. Welker TELEPHONE NO. 291-9502

(This space for State Use)

Original Signed by CHARLES GHOLSON

DEPUTY OIL & GAS INSPECTOR, DIST. #3

APPROVED BY _____ DATE OCT 07 1991

CONDITIONS OF APPROVAL, IF ANY:

TOP PLUG 100' MINIMUM

WELL # State #20

A Sec. 28 T. 20 N., R 9 W McKinley County
990' From N line, 1315 From E. line

Casing: $4\frac{1}{2}"$ @ 543' GR.

Perfs.: 295-315, 496-503

T.D. 593' GR.

