

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other
2. NAME OF OPERATOR  
T. L. MORRIS
3. ADDRESS OF OPERATOR  
P. O. Box 1038, Kilgore, Texas 75662
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17  
below.) 2310 FWL 990 FSL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- |                      |                          |
|----------------------|--------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/> |
| FRACTURE TREAT       | <input type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input type="checkbox"/> |
| REPAIR WELL          | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> |
| MULTIPLE COMPLETE    | <input type="checkbox"/> |
| CHANGE ZONES         | <input type="checkbox"/> |
| ABANDON*             | <input type="checkbox"/> |

(other) Report of spudding and  
setting surface casing

## SUBSEQUENT REPORT OF:

- |                                     |
|-------------------------------------|
| <input type="checkbox"/>            |
| <input type="checkbox"/>            |
| <input checked="" type="checkbox"/> |
| <input checked="" type="checkbox"/> |
| <input type="checkbox"/>            |
| <input type="checkbox"/>            |
| <input type="checkbox"/>            |

REPORT OF:    
 RECEIVED  
 JUN 26 1961  
 (NO. 8)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well on May 30, 1981. Set new 20" 8 5/8 surface casing at 150' circulating 75 sx common cement to surface on May 31, 1981.



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John D. Chua TITLE Agent DATE June 13, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

МОСС

\*See Instructions on Reverse Side

JUN 16 1966

BY Dean Elliott