

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

<p>1. Type of Well Oil</p> <hr/> <p>2. Name of Operator Robert L. Bayless</p> <hr/> <p>3. Address & Phone No. of Operator P.O. Box 168, Farmington, NM 87499</p> <hr/> <p>4. Location of Well, Footage, Sec., T, R, M 660' FSL & 660' FEL, Unit P Sec. 20, T-16-N, R-6-W, NMPM, McKinley County</p>	<p>API # (assigned by OCD) 30-031-20693</p> <p>5. Lease Number</p> <p>6. State Oil&Gas Lease # 0-9725</p> <p>7. Lease Name/Unit Name Santa Fe Pacific RR</p> <p>8. Well No. #41</p> <p>9. Pool Name or Wildcat Gallup</p> <p>10. Elevation: 6408' GL</p>
---	---

RECEIVED
SEP 22 1999
OIL CON. DIV.
DIST. 3

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -

13. Describe Proposed or Completed Operations

Robert L. Bayless plugged and abandoned this well on August 12, 1999.

8-5-99 Road rig and to location, muddy location. Spot and level rig on location; kept sinking.

8-11-99 Chain up all equipment at haul road and road to 2nd wash. Wait for backhoe to repair wash; 15' washout. Road rig and equipment to location, RU. ND wellhead and NU BOP, test. TOH with 21 joints 2-3/8" tubing and packer; LD. TIH with tubing and tag bottom at 732'. Circulate hole clean with 3 bbls water. Plug #1 with 22 sxs Class B cement from 732' to 448'. TOH with tubing and WOC. SI well and SDFD.

8-12-99 Safety meeting. TIH and tag cement at 481'. TOH and LD tubing. Load casing with 2 bbls water and attempt to pressure test, leak. Perforate 2 squeeze holes at 100'. PU 4 joints tubing and TIH to 130'. Plug #2 with 16 sxs Class B cement with 2% CaCl₂ from 130' to surface, circulate good cement returns out casing valve. Shut in valve then pump 8 sxs cement with 2% CaCl₂ with good returns around 4-1/2" casing. Total cement, 24 sxs with 2% CaCl₂. TOH and LD tubing. Shut in well and WOC. Tag cement 3' from surface. ND BOP, dig out and cut off 4-1/2" casing; cement at surface. Mix 8 sxs Class B cement and install P&A marker. RD rig; move off location. H. Villaneuva, NMOCD, was on location.

SIGNATURE Tom McCarthy Engineer September 14, 1999

(This space for State Use)
Approved by E. Villaneuva Title DEPUTY OIL & GAS INSPECTOR, DIST. 3

SEP 22 1999