

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-031-20705
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SANTA FE PACIFIC RAILROAD
8. Well No. 47
9. Pool name or Wildcat Miguel Creek Gallup

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well OIL WELL ☒ GAS WELL ☐ OTHER: ☐	
2. Name of Operator ROBERT L. BAYLESS	
3. Address of Operator P.O. BOX 168 FARMINGTON, NM 87499	
4. Well Location Unit Letter <u>L</u> : <u>2310</u> Feet from the <u>SOUTH</u> Line and <u>330</u> Feet from The <u>WEST</u> Line Section <u>21</u> Township <u>16N</u> Range <u>6W</u> NMPM <u>McKINLEY</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6477 GR	


11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO :	SUBSEQUENT REPORT OF :
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒	REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☐
OTHER: ☐	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Robert L. Bayless intends to plug and abandon this well by June 1, 2003. The procedure is attached.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

ENGINEER

DATE

6/6/02

TYPE OR PRINT NAME

Tom McCarthy

TELEPHONE NO.

(505) 327-2659

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERSON

DEPUTY OIL & GAS INSPECTOR, DIST. 9

APPROVED BY

TITLE

DATE

JUN 10 2002

CONDITIONS OF APPROVAL, IF ANY:

Robert L. Bayless

Plug and Abandon Procedure

SFPRR No. 47

2310' FSL & 330' FWL, Section 21, T16N, R6W

McKinley County, NM

Well data:

Surface Casing: None.

Production Casing: 5.5" 14# casing set at 865'. Cemented with 125 sxs.

TD: 865'

PBD: 865'

Perfs: 842-52'.

Tubing: 2 3/8" 810'.

Rods: 808'.

1. Install rig anchors if necessary. Dig small workover pit if necessary.
2. Move in rig.
3. If well has rods, unseat pump and move rods to see if they are free. Reseat pump and pressure test tubing to 1000 PSI. Trip out laying down rods and pump.
4. Pick up extra tubing and tag PBD. Trip out and tally tubing. Inspect tubing. Pick up work string if necessary.
5. Trip in with tubing open ended to 852'. Circulate casing clean. Spot balanced **Cement Plug No. 1** (see volume below) down tubing. Trip out above cement and WOC. Trip in and tag cement. Spot additional plug if necessary.
6. Trip out with tubing.
7. Rig up wireline. Perforate 3 squeeze holes at 100'. Attempt to establish circulation out the bradenhead (if there is one) or outside the production string to the surface. Mix cement for **Cement Plug No. 2** (see volume below) and pump down casing, attempting to circulate to surface. Shut in and WOC.
8. Cut off casing. Fill casings with cement if necessary. Install P & A marker. Rig down and move off.

Cement Plug No. 1: 19 sx.

Cement Plug No. 2: 41 sx.

Notes: All cement will be Class B Neat.

Other than the cement, the well bore fluid will be 8.3 PPG water.

All cement volumes will be 100% excess outside casing and 50' excess inside casing.