

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator Tesoro Petroleum Corp.	8. Farm or Lease Name Santa Fe Railroad "A"
3. Address of Operator 2000 1st of Denver Plaza, Denver, CO 80202	9. Well No. 92
4. Location of Well UNIT LETTER P 1060 FEET FROM THE South LINE AND 1550 FEET FROM THE East LINE, SECTION 1 TOWNSHIP 17N RANGE 9W NMPM.	10. Field and Pool, or Wildcat S. Hospah Field Lower Hospah Sand
15. Elevation (Show whether DF, RT, GR, etc.) 6997' GL	12. County McKinley


Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PLATFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD @ 1864 ft., Lower Hospah Top at 1744', Upper Hospah @ 1688'.

- Clean out 7 7/8" hole to 1800 ft.
- Run in tubing and cement from 1780-1650 ft. (130 ft.) with 50 sacks class "B" cement.
- Pull tubing up to 60 ft. (8 5/8" surface csg. at 43 ft.) and cement to surface with 20 sacks class "B" cmt.
- Install dry hole marker and restore drill site.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Frank T. Chavez TITLE District Operations Manager DATE 11/18/81

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 3

DATE NOV 20 1981