

DEPARTMENT OF THE INTERIOR (Other Instructions on Reverse Side)
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM-34581-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chico Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 26, T17N, R6W

12. COUNTY OR PARISH 13. STATE

McKinley

NM

1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Colorado Plateau Geological Services, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 537, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

2310' FNL, 1750' FEL, Sec. 26, T17N, R6W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6435 GR

16. Check Appropriate Box To Indicate Nature of Report, for Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

REILL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was spud on October 15th, 1982. 121' of 7" casing was set with cement to the surface (17# K-55). Well was drilled to total depth of 2750' on Wednesday, October 20th, 1982. Well was T.D.'d in Burro Canyon.

Upon verbal approval of Steve Mason on the 20th, the well was plugged and abandoned with cement plugs set as follows:

100' from 2510' to 2410'

175' from 1650' to 1475'

100' from 425' to 325'

170' from 170' to surface

Mud was left between each plug.

The well was logged from 2734' to 150' with gamma ray and resistivity logs.

RECEIVED

SEP 26 1983

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE President

DATE

Oct 21 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side