(other) Spud, set surface csg.

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NM 17184			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME			
1. oil 🖂 gas 🗇	Bird Federal	_		
well XX well other	9. WELL NO.			
2. NAME OF OPERATOR	12-11	_		
Pird Oil Corp c/o Bayless Drilling	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR WAS	destildcat Mesaverde			
P.O. Box 2669, Farmington, NM 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA			
helow)	Sec. 12, T19N, R5W			
AT SURFACE: 2310' FSL & 1650' FWL (NESW)	12. COUNTY OR PARISH 13. STATE			
AT TOP PROD. INTERVAL: same	McKinley New Mexico			
AT TOTAL DEPTH: same	14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,				
REPORT, OR OTHER DATA	15. ELEWATIONS (SHOW DF, KDB, AND WD)			
OURSEQUENT REPORT OF	6364 CL	_		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	JED \			
TEST WATER SHUT-OFF				
FRACTURE TREAT	1890			
SHOOT OR ACIDIZE REPAIR WELL	(NOTE: Report results of multiple completion or zo	one		
PULL OR ALTER CASING	15. FLEWATIONS (SHOW DF, KDB, AND W. 1983) (NOTE: Report results of multiple completion or 20, 1984)			
	11 J 10			

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
 - 4-6-83 227' Drilling. Spud well at 5:30 p.m. 4-5-83. Drilled 94' of Ran 94' of 8-5/8" surface casing. Cemented 12¼" surface hole. surface with 94.4 ft³ (80 sx) of Class B cement with 2% CaCl₂. circulation throughout job. Plug down at 7:15 p.m. 4-5-83.

.. . 12 1983

OIL CON. DIV. DIST 3

		_	
Subsurface Safety Valve: Manu. and Type		Set @	Ft.
18. I hereby certify that the foregoing is true and correct SIGNED	DATE	April 6, 1983	· · · · · · · · · · · · · · · · · · ·
(This space for Federal or State office use)			
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE		

AGGEF IED FOR RECORD

*See Instructions on Reverse Side

APR 08 1983

