

cc: 5 BLM, 1 Well File

Form 3160-5  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED  
MAR 26 1992  
OIL CON. DIV.  
DIST. 3

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.  
NM-7509

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. Fed. 28  
Oak Spring #1 #2

9. API Well No.  
30-031-20949

10. Field and Pool, or Exploratory Area  
Ojo Encino Entrada

11. County or Parish, State  
McKinley, NM

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
MERRION OIL & GAS CORPORATION

3. Address and Telephone No.  
P. O. Box 840, Farmington, NM 87499 505/327-9801

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 28, T20N, R5W  
2310' FSL & 790' FEL  
1900 1650

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☒ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Request approval to cancel sidetrack plans submitted on Sundry dated 3-20-92 and, instead, to plug and abandon wellbore by placing cement plugs as follows:

| Plug Depth | Sx  | Cu Ft | Formation Covered |
|------------|-----|-------|-------------------|
| 5900-6109' | 50  | 60    | Entrada           |
| 4700-5150' | 250 | 295   | Dakota-Morrison   |
| 3470-3570' | 43  | 50    | Gallup            |
| 1120-1220' | 43  | 50    | Mesaverde         |
| 390-490'   | 47  | 55    | Pictured Cliffs   |
| 204-304'   | 37  | 44    | Surface Shoe      |
| 0-50'      | 18  | 22    | Surface Plug      |

RECEIVED  
BLM  
92 MAR 24 PM 3:00  
JIS FARMINGTON, N.M.

Will place drilling mud between plugs. Release drilling rig. (per verbal Mr. Errol Beecher, 3-20-92)

Will install dry hole marker and reclaim surface as required by the SMA.

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct.

Signed \_\_\_\_\_ Title \_\_\_\_\_ Engineer

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_  
Conditions of approval, if any:

APPROVED

Date 3/23/92

MAR 25 1992

AREA MANAGER