

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Lease Name or Unit Agreement Name Santa Fe
2. Name of Operator Enerdyne Corporation	8. Well No. 205
3. Address of Operator P.O. Box 502 Albuquerque, N.M. 87103	9. Pool name or Wildcat Chaco Wash Mesa Verde
4. Well Location Unit Letter <u>P</u> : <u>265</u> Feet From The <u>South</u> Line and <u>445</u> Feet From The <u>East</u> Line Section <u>21</u> Township <u>20N</u> Range <u>9W</u> NMPM <u>McKinley</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6423' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ PULL OR ALTER CASING ☐ OTHER: <u>Spud</u> ☒	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐ CASING TEST AND CEMENT JOB ☐ OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/ 8/92 12:15 Pm Spud the Santa Fe # 205 well drilling a 6 1/4" hole.
10/12/92 9:15 Am Start coring at 309'GR
10/14/92 4:50 Pm Stop coring at 341'GR. Cut 32' of core, recover 21' of core.
10/15/92 8:30 Am Ream hole with a 6 1/4" bit to 341'GR and drill to TD
12:45 Pm TD well at 357'GR
2:10 Pm Log well from TD to surface with a dual induction density, gamma ray, Sp.
10/16/92 8:30 Am Ran 11 Jts. 4 1/2", 10.50 lb /ft, J-55 casing
Casing at 348.51'GR
Guide shoe top at 347'GR
Cement with 40 sks (62cu ft) Class 'B', 4% gel
Plug down at 11:15 am on 10/16/92
Circulated 1/2 Bbl cement to surface

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Frank Welker TITLE Vice President DATE 10/16/92
TYPE OR PRINT NAME Frank Welker TELEPHONE NO. 291-9502

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DATE OCT 24 1992
CONDITIONS OF APPROVAL, IF ANY