District II 811 South First, Artesia, NM 87210 District III 811 South First, Artesia, NM 87210 District III 810 South Pacheco District III 811 South First, Artesia, NM 87210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 2040 South Pacheco, Santa Fe, NM 87505 SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS OIL CONSERVATION DIVISION STATE X FEE 6. State Oil & Gas Lease No. 24580 7. Lease Name or Unit Agreement N Fajada State 2 The proposals.) 1. Type of Well: Oil Well X Gas Well Other 2. Name of Operator Synergy Operating LLC 3. Address of Operator P.O. Box 5513, Farmington, NM 87499 Unit Letter N : 395 feet from the South line and 1820 feet from the West			of New Mex			Form C
DISTRICT NO. 100 No. 1		0. /	Energy, Minerals and Natural Resources		WELL API'NO	Revised March 25,
811 South Frest, Arreisa, NM 87210 DEMORTH BURNERS RJ. Ardie, NM 87410 Santia Fe, NM 87505 Santia Fe, NM 8			OIL CONCEDUATION DIVICION			
Santa Fe, NM 87405 Santa Fe, NM 87505 Santa F	811 South First, Artesia, NM 87210	0				
DEBUTES IT WAS ADDRESS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS. 1. Type of Well: Oil Well X Gas Well Other North Report of Well One Synergy Operating LLC 3. Address of Operator PO.Box \$513, Farmington, NM 87499 Unit Letter N : 305 feet from the South line and 1820 feet from the West Well Coation Unit Letter N : 305 feet from the South line and 1820 feet from the West Nortice Report or Other Data Section 2 Township 20N Range 11W NMPM McKinley Co 6365 (RG 6377 RKB) 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON SUBSEQUENT REPORT OF: REMEDIAL WORK ALTER CASING MULTIPLE COMPLETION OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated or recompilation or recompilation. Sputa 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-14" Surface Hole from surface to TD @ 320'. Run 9-5/8" landing it. Estatic, Pump 15-BBLS FW as spacer, Cmrl 49-5/8" Cag w 200-sas CL 18+2% Cacl2+ 1/4#/sx Cellofake @ 4.5-BPM & 101-64-18-18-18-18-18-18-18-18-18-18-18-18-18-	District III 1000 Rio Brazos Rd., Aztec, NM 8	7410				
COO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEPENDEN OF PLICE BACK TO A DEPENDENCY BETWEEN THE FORM C-101 FOR SUCH PROPOSALS.) 1. Type of Well:	District IV	Santa	1 FE, INIVI 0/2	03		as Lease No.
1. Type of Well: Oil Well X Gas Well Other	(DO NOT USE THIS FORM FOR DIFFERENT RESERVOIR. USE	PROPOSALS TO DRILL OR TO I	DEEPEN OR PLUC	BACK TO A		
2. Name of Operator 3. Address of Operator P.O.Box 5513, Farmington, NM 87499 4. Well Location Unit Letter N : 395 feet from the South Indicate Name of Notice, Report or Other Data Section 2 Township 20N Range 11W NMPM McKinley Co 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6365' GR, 6377' RKB 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASIL TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS COMMENCE DRILLING OPNS CHEMETIAN OF COMPLETION CHANGE PLANS 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimates of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completor recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notche Collar as guide shoc, 7-1ts 9-5/8" 36r J-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Estate Circ, Pump 15-BBLS FW as spacer, Cmt'd 9-5/8" Csg w/ 200-sxs CL' B' + 2% Cacl-2 + 1/48/sx Celloflake @ 4.5-BPL & Wn. 125-5HRs on St. 28.999 w/ 1104/cri 11-BBLS Grie To BBLS Wn. 125-5HRs on St. 28.999 w/ 1104/cri 11-BBLS Grie To BBLS Grie To BBLS Grie To BBLS Wn. 125-5HRs on St. 28.999 w/ 1104/cri 11-BBLS Grie To BBLS Grie To BBLS Wn. 125-5HRs on St. 28.999 w/ 1104/cri 11-BBLS Grie To BBLS Wn. 125-5HRs on St. 28.999 w/ 1104/cri 11-BBLS Grie To BBLS Grie T	1. Type of Well:	Wall D Other	0) 医(CENNE	À	
Synergy Operating LLC Synergy Operation Synergy Operation Synergy Operator Po.Bos 5513, Farmington, NM 87499 ODIT GOIL GOIL Wildcat		well Li Other	m .		Well No	
3. Address of Operator P.O.Box 5513, Farmington, NM 87499 4. Well Location Unit Letter N : 395 feet from the South line and 1820 feet from the West Section 2 Township 20N Range 11W NMPM McKinley Co 10. Elevation (Show whether DR. RKB, RT, GR, etc.) 6365° GR, 6377° RKB 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON SUBSEQUENT REPORT OF: REMEDIAL WORK ALTER CASING MULTIPLE COMPLETION OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed comple or recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notche Collar as guide shoe, 7-1st 9-5/8" 36# 1-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" landing It. Estatic; Pump 15-BBLS FW as spacer, Cmt 49-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% CaCl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4#/sx Celloflake @ 4-5/8" Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4#/sx Celloflake @ 4-5/8* Csg w 200-sxs CL "B+ 2% Cacl-2+ 1/4	-		J.	N 1 8 1999	1	
Unit Letter N : 395 feet from the South line and 1820 feet from the West Section 2 Township 20N Range 11W NMPM McKinley Co 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6365' GR, 6377' RKB 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ABANDON ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ABANDON ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ABANDONMENT CASING TEST AND CEMENT JOB OTHER: DOTHER: DOTHER: DOTHER: DOTHER: DOTHER: DOTHER: DOTHER: COMPLETION CEMENT JOB OTHER: DOTHER:	3. Address of Operator		OAIL (SOM Ends		Wildcat
Unit Letter N : 395 feet from the South line and 1820 feet from the West Section 2 Township 20N Range 11W NMPM McKinley Co 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6365 GR, 6377 RKB 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASH TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CEMENT JOB OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimates of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completor recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notche Collar as guide shoe, 7-Jts 9-5/8" 36# 1-55 ST&C Csg (302.75') w' 2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Estaticine, Pump 1-5-BBLS FW as spacer, Cmt' 9-5/8" CSg (302.75') w' 2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Estaticine, Pump 1-5-BBLS FW as spacer, Cmt' 9-5/8" CSg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Tresult Rams, Csg &		3ton, 14141 07477		DIBIL B		
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6365' GR, 6377' RKB 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASIR TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimates of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completor recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notche Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" Notche Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" Notche Collar as guide shoe, 7-Jts 9-5/8" StW r, plug down @ 12:55-HST son 5/28/99 w/ 110#, circ 11-BBLS Cmt to surf (52-sx8). Consteady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressu Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt. Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK. Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE	Unit Letter <u>N</u>	: <u>395</u> feet from t		-	0feet from	the <u>West</u>
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASH TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completor or recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notch Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Estaticire, Pump 15-BBLS FW as spacer, Cmt* 04-9-5/8" Csg w/ 200-sxs CL. 18+2% CaCl-2+1/4//sx Celloflake @ 4.5-BPM & 100-2 displaced wooden plug w/ 21.5-BBLS wfty nly glown @ 12:55-HST son 5/28/99 w/ 110#, circ 11-BBLS Cmt to surf (52-sxs). Cn steady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressu Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt. Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK. Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE	Section 2	Townshir	20N	Range 11W	NMPM	McKinley Cou
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASIR TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CASING TEST AND CEMENT JOB OTHER: 12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed complete or recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notche Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Estaticire, Pump 15-BBLS FW as spacer, Cmt'd 9-5/8" Csg w/ 200-sxs CL 'B' + 2% CaCl-2 + 1/4#/sx Celloflake @ 4.5-BPM & 100-2 displaced wooden plug w/ 21.5-BBLS Wtr, plug down @ 12:55-Hrs on 5/28/99 w/ 110#, circ 11-BBLS Cmt to surf (32-sxs). Cn steady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressu Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt. Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE		10. Elevation (She	ow whether DR,	RKB, RT, GR, etc.)		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS ABANDONMENT CASING TEST AND CEMENT JOB OTHER: CASING TEST AND CEMENT JOB CHENT JOB COMPLETION COMPLETION CHENT JOB COMPLETION COMPLETION CHENT JOB COMPLETION COMPLETION CHENT JOB COMPLETION CHENT JOB COMPLETION CHENT JOB COMPLETION COMPLETION CHENT JOB CALL JURIS CHENT JOB CALL	11. Cł			ure of Notice, Ro	eport or Other	Data
TEMPORARILY ABANDON	NOTICE (OF INTENTION TO:		SUBS	EQUENT RE	PORT OF:
PULL OR ALTER CASING MULTIPLE COMPLETION CEMENT JOB OTHER: OTHER: OTHER: OTHER: CASING TEST AND CEMENT JOB OTHER: OTHER: CASING TEST AND CEMENT JOB OTHER: OTHER: CASING TEST AND CEMENT JOB ABANDONMENT ABANDONME	PERFORM REMEDIAL WO	RK PLUG AND ABANE	DON 🗆	REMEDIAL WORK		ALTERING CASIN
OTHER: CEMENT JOB OTHER:	TEMPORARILY ABANDON	☐ CHANGE PLANS		COMMENCE DRILL	ING OPNS.	
12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completor recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notche Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Estatcire, Pump 15-BBLS FW as spacer, Cmt'd 9-5/8" Csg w/ 200-sxs CL 'B' + 2% CaCl-2 + 1/4#/sx Celloflake @ 4.5-BPM & 100-2 displaced wooden plug w/ 21.5-BBLS Wtr, plug down @ 12:55-Hrs on 5/28/99 w/ 110#, circ 11-BBLS Cmt to surf (52-sxs). Cn steady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressu Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK. Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Operations Manager DATE 6/9/99 Type or print name Glen O. Papp Telephone No. 325-	PULL OR ALTER CASING				. 🛚	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completor recompilation. Spud 12-/14" surface hole @ 05:15 AM on 5/28/99. Drill 12-1/4" Surface Hole from surface to TD @ 320'. Run 9-5/8" Notched Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Establicine, Pump 15-BBLS FW as spacer, Cmt'd 9-5/8" Csg w/ 200-sxs CL 'B' + 2% CaCl-2 + 1/4#/sx Celloflake @ 4.5-BPM & 100-2 displaced wooden plug w/ 21.5-BBLS Wtr, plug down @ 12:55-Hrs on 5/28/99 w/ 110#, circ 11-BBLS Cmt to surf (52-sxs). Cn steady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressu Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt. Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK. Thereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Operations Manager DATE 6/9/99 Type or print name Glen O. Papp Telephone No. 325-						
Collar as guide shoe, 7-Jts 9-5/8" 36# J-55 ST&C Csg (302.75') w/ 2-Centralizers & land Csg @ 318' on 9-5/8" landing Jt. Establicirc, Pump 15-BBLS FW as spacer, Cmt'd 9-5/8" Csg w/ 200-sxs CL 'B' + 2% CaCl-2 + 1/4#/sx Celloflake @ 4.5-BPM & 100-2 displaced wooden plug w/ 21.5-BBLS Wtr, plug down @ 12:55-Hrs on 5/28/99 w/ 110#, circ 11-BBLS Cmt to surf (52-sxs). Cn steady at surface. WOC 12-Hrs. NU 11" 3M X 9-5/8" Csg Head. NU 11" 3M Shaffer LWS BOP, kill spool, & manifold Pressu Test Blind Rams, Csg & Manifold To 200# For 5-MINS, Held OK. Run 1-Jt DP w/ TIW VALVE & Test Pipe Rams, Csg, Cmt of Manifold to 200# for 5-MINS, OK, Then To 1000# for 10-MINS, HELD OK. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Operations Manager DATE 6/9/99 Type or print name Glen O. Papp Telephone No. 325-	of starting any proposed	completed operations. (Clear d work). SEE RULE 1103.	rly state all perti For Multiple Co	nent details, and given pletions: Attach	e pertinent dates, wellbore diagram	including estimated of proposed comple
I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE Operations Manager Type or print name Glen O. Papp Telephone No. 325-	Collar as guide shoe, 7-Jts 9 circ, Pump 15-BBLS FW as displaced wooden plug w/ 2 steady at surface. WOC 12-Test Blind Rams, Csg & Ma	9-5/8" 36# J-55 ST&C Csg (3 s spacer, Cmt'd 9-5/8" Csg w 21.5-BBLS Wtr, plug down (6 -Hrs. NU 11" 3M X 9-5/8" (anifold To 200# For 5-MINS	302.75') w/ 2-Ce // 200-sxs CL 'E @ 12:55-Hrs on Csg Head. NU S, Held OK. Ru	entralizers & land Cs ! + 2% CaCl-2 + 1/4 5/28/99 w/ 110#, cii 11" 3M Shaffer LWi n 1-Jt DP w/ TIW V	sg @ 318' on 9-5/9 #/sx Celloflake @ cc 11-BBLS Cmt S BOP, kill spool	8" landing Jt. Establ
SIGNATURE TITLE Operations Manager DATE 6/9/99 Type or print name Glen O. Papp Telephone No. 325-						
SIGNATURE TITLE Operations Manager DATE 6/9/99 Type or print name Glen O. Papp Telephone No. 325-					W	
Type or print name Glen O. Papp Telephone No. 325-					W	
(This was for State use)	I hereby certify that the info	rmation above is true and co	omplete to the b	est of my knowledge		
(This space for State USA) SIGNED BY CHAPLE T PERCENT	\mathcal{A}	ormation above is true and co			and belief.	DATE <u>6/9/99</u>
TO THE PROPERTY OF A CONTRACT OF PROPERTY OF A SAME INCOME. IN THE SECOND OF THE PROPERTY OF A SAME INCOME.	SIGNATURE Type or print name	Glen O. Papp	TITLE		and belief.	