

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE **FAIRMINGTON, NM**

5. Lease Designation and Serial No.

14-20-603-3177

6. If Indian, Allottee or Tribe Name

011362 (261)

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Betty B 1

9. API Well No.

30039050820000

10. Field and Pool, or Exploratory Area

Lybrook Gallup

11. County or Parish, State

Rio Arriba, New Mexico

2. Name of Operator

Celsius Energy Company

3. Address and Telephone No.

1331 17th Street, Denver, CO 80202

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

585' FNL & 2275' FWL Sec. 15, T23N-R7W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Celsius Energy Company submits this plan to permanently plug and abandon this well as per proposed plugging program.

1. Set cast iron bridge plug at 5464'.

2. Run tubing in the hole - spot 26 sack cement plug - 5231' - 5464' inside 4 1/2" casing.

3. Perforate 4 1/2" casing at 3751'. Wireline set cement retainer at 3700'.

4. Run tubing in the hole. Pump 50 sack cement plug - 3651' - 3761' annulus plug - 50' casing plug.

5. Perforate 4 1/2" casing at 2236'. Wireline set cement retainer at 2186'.

6. Run tubing in the hole. Pump 111 sack cement plug 1882' - 2236' annulus plug - 50' casing plug.

7. Perforate 4 1/2" casing at 1729'. Wireline set cement retainer at 1675'.

8. Run tubing in the hole. Pump 113 sack cement plug 1495' - 1729' annulus plug - 50' casing plug.

9. Attempt to pump down 8 5/8" x 4 1/2" annulus. Pump 42 sack cement plug - surface to 206'.

10. If unable, pump down the annulus. Run in the hole with 2 3/8" tubing. Pump 16 sack cement plug - 206' to surface.

11. Cut off the wellhead.

12. Run 50' of 1" pipe inside 8 5/8" x 4 1/2" annulus. Circulate cement to surface.

13. Install dry hole marker as per BLM specifications.

14. I hereby certify that the foregoing is true and correct

Signed

E. J. Marsh

Title

Dist. Prod. Superintendent

Date

10-10-97

(This space for Federal or State office use)

Approved by

/S/ Duane W. Spencer

Title

Date

OCT 16 1997

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD