
5 USGS

0	7-1-7
2	н не

Ļ	SO.	Union
Ļ	SO.	Union

## (SUBMIT IN TRIPLICATE)

Bi Aj	ndget Bureau No. 42-R358.4. oproval expires 12-31-60.
Land Office	Santa Fe
Lease No.	SF 078272-A
Unit	



## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

NOTICE OF INTENTION TO DRILL.	SUBSEQUENT REPORT OF WATER SHUT-OFFX
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MAR	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	March 13 19 6
Campos	, 17
Well No. 1-10 is located 1650ft. from	m. ${\mathbb{N} \choose {\mathbb{S}}}$ line and ${1650 \choose {\mathbb{N}}}$ ft. from ${\mathbb{E} \choose {\mathbb{N}}}$ line of sec. ${10 \choose {\mathbb{N}}}$
NW/4 SE/4 Sec. 10 23N (1/4 Sec. and Sec. No.) (Twp.)	7W NMPM (Range) (Meridian)
, (= "F")	(Range) (Meridian) Arriba New Mexico
(Field) (County	or Subdivision) (State or Territor)
Ground Level	/ ************************************
The elevation of the klarkick shows above sea le	evel is 7264.5t.
	MAK 1 7 15
DETA	ILS OF WORK
DETA (State names of and expected depths to objective sands; show air ing points, and all	ILS OF WORK  CIL CON  City Construction of proposed casings; indicate mudding the semant other important proposed work)
OETA (State names of and expected depths to objective sands; show sing points, and all dded 10:00 P. M., 3-2-61. Drilled 1: , J-55, 8 Rd., ST&C casing. T.E. 1 . plus 2% CaCl. P.O.B. 2:30 A.M.	AILS OF WORK    Izes, weights, and lengths of proposed casings; indicate mudding)   Semest other important proposed work    2-1/4" hole to 205' ran 6 jts. 8-5/8" O.D. 87.35' set @ 199' RKB cemented w/130 sx 3-3-61. Drilled 7-7/8" hole to 5905' ran ST&C casing. T.E. 5925.65' set at 5905
OETA  (State names of and expected depths to objective sands; show all ing points, and all dded 10:00 P. M., 3-2-61. Drilled 13, J-55, 8 Rd., ST&C casing. T.E. 15. plus 2% CaCl. P.O.B. 2:30 A.M. jts. 4-1/2" O.D., 9.5#, J-55, 8 Rd. B. cemented w/100 sx 6% gel & 50 sx	izes, weights, and lengths of proposed casings; indicate midding by same other important proposed work)  2-1/4" hole to 205' ran 6 jts. 8-5/8" O.D. 87.35' set @ 199' RKB cemented w/130 sx 3-3-61. Drilled 7-7/8" hole to 5905' ran. ST&C casing. T.E. 5925.65' set at 5905 neat. P.O.B. 3:45 PM, 3-11-61.