



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. **3P-078493-A**

Unit _____

RECEIVED

JUN 5 1959

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL _____	SUBSEQUENT REPORT OF WATER SHUT-OFF _____
NOTICE OF INTENTION TO CHANGE PLANS _____	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING _____ X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF _____	SUBSEQUENT REPORT OF ALTERING CASING _____
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL _____	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR _____
NOTICE OF INTENTION TO SHOOT OR ACIDIZE _____	SUBSEQUENT REPORT OF ABANDONMENT _____
NOTICE OF INTENTION TO PULL OR ALTER CASING _____	SUPPLEMENTARY WELL HISTORY _____
NOTICE OF INTENTION TO ABANDON WELL _____	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 5, 1959

Yarborough-Federal
Well No. **1** is located **500** ft. from **[N]** line and **530** ft. from **[W]** line of sec. **10**
NW 1/4 of Sec. 10 **23-N** **6-W** **NM PM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Undesignated **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **5732** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 5550'. Plugged back depth 5533'.

Perforated 5-1/2" casing from 5434' to 5456' and 5512' to 5524' with 4 jet shots per foot. Ran tubing to 5524' with packer set at 5346' and washed perforations with 500 gallons mud acid. Pulled tubing and treated perforations through casing with 20,000 gallons crude oil containing 30,000# sand.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **The Texas Company**

Address **P. O. Box 317**

Parlington, N. M.

By *[Signature]*

Title **Dist. Sup't.**