Form 9-331 b (April 1952)				
1		;	 -	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency	_
Jicarilla Triba	1
Allotte Jicarilla "D"	
Lease No. Contract #44	
Tract #91	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTERVION TO DEBIL. NOTICE OF INTERVION TO CHANGE PIANS. NOTICE OF INTERVION TO REDRILL OR REPAIR WILL SUBSEQUENT REPORT OF SHOTING OR ACIDIZING. NOTICE OF INTERVION TO REDRILL OR REPAIR WILL SUBSEQUENT REPORT OF REDRILLING OR REPAIR. NOTICE OF INTERVION TO SHOOT OR ACIDIZE. NOTICE OF INTERVION TO ABANDON WELL SUPPLEMENTARY WELL HISTORY. NOTICE OF INTERVION TO ABANDON WELL Jicarilla "D" July 30, 19.55. Well No. 1 is located 920 ft. from S line and 930 ft. from W line of sec. 6. No. M. P. M. (46 Sec and Sec No.) (Typ.) (Change) (Micridian) Wildeat Rio Arribs New Mexico (7044) (Country or Schddvision) (Change) (Micridian) When Mexico (7044) (Country or Schddvision) (Change) (Micridian) (Country or Schddvision) (Change) (Ch					
NOTICE OF INTENTION TO IEST WATER SHUT-OFF. NOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO RULL OR ALTER CASING. NOTICE OF INTENTION TO REPAIR. I is located 990 ft. from \$small representation of the comment of the	NOTICE OF INTENTION TO DRI	щ	SUBSEQUENT REP	ORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO SH	NOTICE OF INTENTION TO CHA	INGE PLANS	SUBSEQUENT REP	ORT OF SHOOTING OR ACIDI	ZING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL	NOTICE OF INTENTION TO TES	T WATER SHUT-OFF	SUBSEQUENT REP	ORT OF ALTERING CASING	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO BEANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) Jicarilla "D" July 30, 19 55 Well No. 1 is located 990 ft. from S line and 990 ft. from W line of sec. 6. SW/4 Sec. 6 23N N. N. M. P. M. SW/4 Sec. 6 23N N. M. M. P. M. (Residue) (Risinge) (Ri	NOTICE OF INTENTION TO REL	ORILL OR REPAIR WELL	Subsequent Rep	ORT OF REDRILLING OR REP	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Jicarilla "D" July 30, 19 55 Well No. 1 is located 990 ft. from S line and 990 ft. from W line of sec. 6. SW/A Sec. 6 23N No. M. M. P. M. (New York) (Reage) (Meridian) Wildcat Ric Arriba (County or Subdivision) (State or Territory) The elevation and superiod depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, commenting points, and all other important proposed work) State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, commenting points, and all other important proposed work) State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, commenting points, and all other important proposed work) Set 200' comment plug from 6950' to 5950' - 4850' to 4750' - 150' plug from 4050' to 3900' - 100' plugs from 2550' to 2450' - 2200' to 2100' - 550' to 450', and a 50' plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4' above the ground lengths of the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and the plan of work must receive approval in writing by the following Subjective and subj	NOTICE OF INTENTION TO SHO	OOT OR ACIDIZE	SUBSEQUENT REP	ORT OF ABANDONMENT	
Jicarilla "D" July 30, 19 55 Well No. 1 is located 990 ft. from S line and 990 ft. from W line of sec. 6 SW/4 Sec. 6 23N N. M. P. M. (Kase, and Sec. No.) (Twp.) (Range) (Meridian) Wildcat Rio Arriba (County or Subdivision) (State or Territory) The elevation aksimum above sea level is 6895 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Set 200° coment plug from 6950° to 6750° Set 100° plugs from 4050° to 3900° - 100° plugs from 2550° to 2450° - 2200° to 2100° - 550° to 450°, and a 50° plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4° above transportant proposed surplement of 11955. I understand that this plan of work must receive approval in writing by the Gridenial Survey Section of ARM NETON, NEW Address. P. 0. Box 426, Farmington, New Maxics By	NOTICE OF INTENTION TO PUL	L OR ALTER CASING	SUPPLEMENTARY	WELL HISTORY	
Jicarilla "D" July 30, 19.55 Well No. 1 is located 990 ft. from S line and 990 ft. from W line of sec. 6. SW/4 Sec. 6 23N N. N. M. P. M. (Mesci and Sec. No.) (Evp.) (Range) (Meridian) Wildcat Rio Arriba New Mexico (Field) (County or Subdivision) (State or Territory) The elevation acceptated depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, camenting points, and all other important proposed work) State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, camenting points, and all other important proposed work) Set 200! cement plug from 6950! to 5950! = 4850! to 4750! = 150! plug from 4050! to 3900! = 100! plugs from 2550! to 2450! = 2200! to 2100! = 550! to 450!, and a 50! plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4! above the ground level ECEIVE AUG 1955 I understand that this plan of work must receive approval in writing by the Gridge Survey Stores opplation family CON. COM. DIST. 3 Address. P. O. Box 426, Farmington, New Mexica	NOTICE OF INTENTION TO ABA	NDON WELL			
Jicarilla "D" July 30, 19.55 Well No. 1 is located 990 ft. from S line and 990 ft. from W line of sec. 6. SW/4 Sec. 6 23N N. N. M. P. N. (Meridian)	<u></u>				
Well No. 1 is located 999 ft. from S line and 990 ft. from E W line of sec. 6. SW/4 Sec. 6 23N N N N P. M. (14 Sec. and Sec. No.) (Pyp.) (Hange) (Mardian) Wildcat Rio Arriba New Mexico (Field) (Country or Subdivision) (State or Territory) The elevation axemetrize flams above sea level is 6895 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and langths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Set 200! coment plug from 6950! to 6750! Set 100! plugs from: 6050! to 5950! - 4850! to 4750! - 150! plug from 4050! to 3900! - 100! plugs from 2550! to 2450! - 2200! to 2100! - 550! to 450!, and a 50! plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4! above the ground level CEVE 1955 NUC 1 1 1955 N	(I	NDICATE ABOVE BY CHECK MARK I	NATURE OF REPORT, NO	OTICE, OR OTHER DATA)	
SW/4. Sec. 6 (4 Sec. and Sec. No.) (Field) (Field) (County or Subdivision) (State or Territory) (State o	Jicarilla "D"			July 30,	, 19 <u>55</u>
(Meridian) (New Mexico (Meridian) (New Mexico (Meridian) (State or Territory) (State or Territory) (State or Territory) (Pip) (State or Territory) (State or	Well No1	is located 990 ft. from	$\mathbf{m} \left\{ \begin{array}{c} \mathbf{K} \\ \mathbf{S} \end{array} \right\}$ line and \mathbf{L}	990ft. from	ine of sec. 6
Wildcat Rio Arriba New Mexico (Field) (County or Subdivision) (State or Territory) The elevation attention and appeted depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) Set 200! cement plug from 6950! to 5950! — 4850! to 4750! Set 100! plugs from: 6050! to 5950! — 4850! to 4750! — 150! plug from 4050! to 3900! — 100! plugs from 2550! to 2450! — 2200! to 2100! — 550! to 450!, and a 50! plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4! above the ground level ECEIVE RELIABLE CON. COM. COM. COM. COM. COM. COM. COM. COM	SW/A Sec. 6	23N	ASH	N. M. P.	M.
The elevation attack and above sea level is _6895 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Set 200' coment plug from 6950' to 6750' Set 100' plugs from: 6050' to 5950' - 4850' to 4750' - 150' plug from 4050' to 3900' - 100' plugs from 2550' to 2450' - 2200' to 3100' - 550' to 450', and a 50' plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4' above the ground level ECEIVE AUGI 1955 AUGI 11955 I understand that this plan of work must receive approval in writing by the Gridesial Survey better operations from 1973. Address P. 0. Box 426, Farmington, New Maxics By C. C. Q. A. C. Paralington, New Maxics		(Twp.)	(Range)	· · · · · · · · · · · · · · · · · · ·	
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Set 200' coment plug from 6950' to 6750' Set 100' plugs from: 6050' to 5950' - 4850' to 4750' - 150' plug from 4050' to 3900' - 100' plugs from 2550' to 2450' - 2200' to 2100' - 550' to 450', and a 50' plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4' above the ground level ECEIVE AUG 1 1955 AUG 1 1955 I understand that this plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of the plan of the plan of work must receive approval in writing by the Grilogical Survey before oppositions for the plan of th	Wildcat	Rio Arrib	8.	New Mexico	
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Set 200! cement plug from 6950! to 6750! Set 100! plugs from: 6050! to 5950! - 4850! to 4750! - 150! plug from 4050! to 3900! - 100! plugs from 2550! to 2450! - 2200! to 3100! - 550! to 450!, and a 50! plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4! above the ground lew ECEIVE AUG 1 1955 I understand that this plan of work must receive approval in writing by the Giplogical Survey Settles operation (ASM) (CON. COM. Company SKELLY OIL COMPANY Address P. 0. Box 426, Farmington, New Mexica	(Field)	(County o	or Subdivision)	(State or To	erritory)
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Set 200! coment plug from 6950! to 6750! Set 100! plugs from: 6050! to 5950! - 4850! to 4750! - 150! plug from 4050! to 3900! - 100! plugs from 2550! to 2450! - 2200! to 2100! - 550! to 450!, and a 50! plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4' above the ground level ECEIVE AUG 1 1955 I understand that this plan of work must receive approval in writing by the Gillogical Survey before operation (ASMINGTON, NEW Address P. 0. Box 426, Farmington, New Mexica	T 1 wheteredo	water from a bassa and law	1: 6805 L		
Set 200! cement plug from 6950! to 6750! Set 100! plugs from: 6050! to 5950! - 4850! to 4750! - 150! plug from 4050! to 3900! - 100! plugs from 2550! to 2450! - 2200! to 2100! - 550! to 450!, and a 50! plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4! above the ground level ECEIVE I understand that this plan of work must receive approval in writing by SKELLY OIL COMPANY Address P. 0. Box 426, Farmington, New Mexics By Region designs, indicate mudding jobs, cementalized, and lengths of proposed casings, indicate mudding jobs, cementalized, and all other important proposed work) SET 100! plugs from 4050! to 4750! - 150! plug from 4050! to 490! to 4750! - 150! plugs from 2550! to 2450! - 2200! to 2100! - 550! to 450!, and a 50! plug on top OI 13-3/8" casing. SEELLY OIL COMPANY DIST. 3 Address P. 0. Box 426, By Region of plugs from 2550! to 4750! - Company Address By Region of plugs from 2550! to 4750! - Company SKELLY OIL COMPANY DIST. 3 Region of plugs from 2550! to 4750! - Region of 13-3/8" casing. Region of 13-3/8" casing. Region of 13-3/8" casing. SEELLY OIL COMPANY DIST. 3 Region of 13-3/8" casing. Region o	ne elevation and management	MACA REAL above sea lev	/ei 18it.		
Set 200' cement plug from 6950' to 6750' Set 100' plugs from: 6050' to 5950' - 4850' to 4750' - 150' plug from 4050' to 3900' - 100' plugs from 2550' to 2450' - 2200' to 2100' - 550' to 450', and a 50' plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4' above the ground level ECEIVE I understand that this plan of work must receive approval in writing by SKELLY OIL COMPANY Address P. 0. Box 426, Farmington, New Mexics By Residue; indicate mudding jobs, cement- ing points, and all other important proposed casings; indicate mudding jobs, cement- ing points, and all elegation of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) 150' plug from 4050' to 5950' to 4750' - 150' plug from 2550' to 24,50' - 2200' to 2100' - 550' to 450', and a 50' plug on top 13-3/8" casing. Set a permanent marker of 4" pipe 4' above the ground level ECEIVE AUG 1 11955 AUG 1 11955 CON, COM. DIST. 3 Address. P. 0. Box 426, Farmington, New Mexics By Residue of proposed work) Set 200' to 4750' - 100' plugs from 2550' to 4750' - 100' plugs from 2550' to 4750' - 100' plugs from 2550' to 450', and a 50' plug on top 1955 AUG 1 11955 AUG 1 11955		DETAI	IS OF WORK		
Set 200° cement plug from 6950° to 6750° Set 100° plugs from: 6050° to 5950° = 4850° to 4750° = 150° plug from 4050° to 3900° = 100° plugs from 2550° to 2450° = 2200° to 2100° = 550° to 450°, and a 50° plug on top of 13-3/8" casing. Set a permanent marker of 4" pipe 4° above the ground lews ECEIVE AUG¹ 1 understand that this plan of work must receive approval in writing by as Gollogical Survey before opposition that the commanded. Company SKELLY OIL COMPANY Address P. 0. Box 426, Farmington, New Mexics By Company Company By Company P. 0. Box 426, By Company By Company Company Company By Company Company Company By Company Co					
I understand that this plan of work must receive approval in writing by the Grological Survey Server operations for the commenced. Company SKELLY OIL COMPANY Address P. 0. Box 426, Farmington, New Mexicos By S. GEOLOG, NEW U.S. GEOLOG, NEW OIL 11955 OON. COM. DIST. 3 By S. C. O. Q. A.L.	Set 100' r 150' plug 2450' - 22 of 13-3/8"	lugs from: 6050° from 4050° to 3900° to 3100° - 550° casing.	to 5950' - 48' - 100' plug' to 450', an	s from 2550' to id a 50' plug on the ground lev	RECEIVED
Farmington, New Mexico	Company SKELLY C	DIL COMPANY	writing by he online	ical Survey Before operations	U. S. GEOLOGICAL SOMEX
Title District Foreman	1 Add: 000				
		on, New Mexica	B	B. E. (Doeper.

\$ - x

•

political section of the section of

.