


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. _____

Unit _____




SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	X	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 23, 1964

Skelly - Federal
Well No. 1 is located 2355 ft. from {N} line and 1510 ft. from {E} line of sec.
NW 1/4 Sec. 1 23N - 1E NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Rio Arriba New Mexico
(Field) (County or Subdivision) (State & Territory)



The elevation of the derrick floor above sea level is 7463.5 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to 34' and set 23' - 9 5/8", 36 casing with 10 sack cement. Continued drilling and set 501' - 7", 20 casing with 125 sack cement at 506'. Drilled to T. D. of 2,513'.

By verbal approval of District Engineer, P. T. McGrath will plug with cement in the following manner, so well can be used as a water well by surface owner.

2513 - 2140 40 sack	1550 - 1450 25 sack
2150 - 2050 25 sack	550 - 450 25 sack

Will install swedge on top.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company P. F. Beeler

Address P. O. Box 1016

Albuquerque, New Mexico

By P. F. Beeler
Operator
Title