



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Sicaria
Tribal
Allottee Sicaria
Lease No. Contract No. 44
Tract No. 91

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<u>Protection I</u>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	RECEIVED
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<u>FEB 5 1958</u>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<u>U. S. GEOLOGICAL SURVEY</u>
NOTICE OF INTENTION TO ABANDON WELL	Report of Perforations	<u>FARMINGTON, NEW MEXICO</u>
	Report of Drill Stem Test No. <u>7</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Sicaria "p"
Well No. 2 is located 990 ft. from N line and 990 ft. from E line of sec. 5
NE 1/4 Section 5 (1/4 Sec. and Sec. No.) 23N (Twp.) 4W (Range) N.M.P.M. (Meridian)
Undesignated (Gallup) (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7082 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run & set $5\frac{1}{2}$ " casing at 6207' with 2-stage tool set at 3813-15'. Cemented around shoe with 250 lbs. reg. cement, 25 Gal. Cemented top section through 2-stage tool set at 3813-15' with 500 lbs. reg. cement, 25 Gal.

Perforated $5\frac{1}{2}$ " casing 6148-69' with 4 jet shots.

DRILL STEM TEST NO. 7 6081-6140', inside $5\frac{1}{2}$ " casing. Testing cement job thru $5\frac{1}{2}$ " casing perforations 6148-69'. Tool open 1 hr. with slight blow of air throughout test. Recovered 210' of water, IPT 350, IPT 700, 30 min. BHP 1050, Hyd. pressure 26500.

Perforated $5\frac{1}{2}$ " casing 5962-72', 5997-6013', 6043-6079', 6069-6075', 6083-6093' & 6139-6148' with 4 Lane Wells jet shots per ft. Total of 69', 276 shots.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY
Box 426
Address Farmington, New Mexico

By (Signed) P. E. Cosper

Title District Superintendent