

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Dyna Ray Gas and Oil Co., Inc. <i>Shaw Alan Oil Co.</i>		8. Farm or Lease Name
3. Address of Operator 4101 E Louisiana, Denver, Colo. 80222		9. Well No. #1 Barry Fed
4. Location of Well UNIT LETTER D 990 FEET FROM THE North LINE AND 1020' FEET FROM THE West LINE, SECTION 3 TOWNSHIP 23N RANGE 1W NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 7335 ground		12. County Rio Arriba


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Remedial work was complete with no results. Request permission to plug and abandon well in the following manner:

50 sacks of cement across the perforations, pull casing, spot 50 sacks of cement in and out of stub of casing, fill hole with mud, place 25 sacks of cement at surface, erect dry hole marker, restore any surface damage.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>H.A. Gurnz</i>	TITLE Manager of Lands	DATE July 16, 1969
APPROVED BY <i>Emmy Clum</i>	TITLE <i>Sgt Dist 111</i>	DATE 7-22-69
CONDITIONS OF APPROVAL, IF ANY:		