For (F	m 9- reb. 19	331 a 351)	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	•	S 7
Lease No.	060230	
Unit	Sep	

-	UNDRY NOTICES AN	
		SUBSEQUENT REPORT OF WATER SHUT-OFF
	ION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENT	ION TO CHANGE PLANS	
NOTICE OF INTENT	ION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF RE-DRILLING OR REPARECEIVEL
NOTICE OF INTENT	TION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENT	TION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENT	TION TO ABANDON WELL	
NOTICE OF INTENT		FARMINGION, WEN
	(INDICATE ABOVE BY CHECK MARK NA	TURE OF REPORT, NOTICE, OR OTHER DATA)
		Mary 29 , 19.57
	is located 190ft. from (Rec. No.) (Rec. No.) (Rec. No.) (County or St.	e New Mexico
The elevation	of the derrick floor above sea level	
	DETAILS d expected depths to objective sands; show sizes, ing points, and all other	S OF WORK , weights, and lengths of proposed casings; indicate mudding jobs, cement- er important proposed work)
(State names of and	DETAILS if expected depths to objective sands; show sizes, ing points, and all other fixtal Depth 5637'. Ran 1 (5625') set at 5637' with 150 secks Posmix, 45 gal; minutes. Top of coment by temperat	s of Work weights, and lengths of proposed casings; indicate mudding jobs, cement- er important proposed work) 135 joints 5 1/2°, 15.5¢, J-55 Casing a 150 sactis regular cement, a 1/b¢ Flocele/Sk. Held 1000 for 30 ture survey at 4100°. Oil CON. COM. DIST. 5
State names of and	DETAILS if expected depths to objective sands; show sizes, ing points, and all other firstal Depth 5637'. Ran 1 (5625') set at 5637' with 150 secks Posmix, 45 gal; minutes. Top of commut by temperate	syriting by the Geological Survey before operations may be commenced.
I understand to	DETAILS i expected depths to objective sands; show sizes, ing points, and all other fixtal Depth 5637'. Ran 1 (5625') set at 5637' with 150 sacks Posmix, 45 gal; minutes. Top of commut by temperat hat this plan of work must receive approval in w	s of Work weights, and lengths of proposed casings; indicate mudding jobs, cement- er important proposed work) 135 joints 5 1/2°, 15.5¢, J-55 Casing a 150 sactis regular cement, a 1/b¢ Flocele/Sk. Held 1000 for 30 ture survey at 4100°. Oil CON. COM. DIST. 5
State names of and	DETAILS I expected depths to objective sands; show sizes, ing points, and all other Total Depth 5637'. Ran I (5625') set at 5637' with 150 secks Posmin, 45 gal, minutes. Top of commit by temperate that this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what the plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what this plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive approval in what the plan of work must receive ap	s of WORK weights, and lengths of proposed casings; indicate mudding jobs, cement- er important proposed work) 135 joints 5 1/2°, 15.5¢, J-55 Casing 150 sacks regular cement, 1/bf Florcele/Sk. Beld 1000 for 30 ture survey at 4100°. OIL CON. CON. OIL CON.
State names of and 6-4-57 I understand to Company	DETAILS i expected depths to objective sands; show sizes, ing points, and all other fixtal Depth 5637'. Ran 1 (5625') set at 5637' with 150 sacks Posmix, 45 gal; minutes. Top of commut by temperat hat this plan of work must receive approval in w	s of WORK weights, and lengths of proposed casings; indicate mudding jobs, cement- er important proposed work) 135 joints 5 1/2°, 15.5¢, J-55 Casing 150 sacks regular cement, 1/bf Florcele/Sk. Beld 1000 for 30 ture survey at 4100°. OIL CON. CON. OIL CON.